#### SPECIAL CONSOLIDATED CHECKLIST

for the

Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999

Notes: 1) This checklist consolidates changes to the Federal code addressed by the following Boilers and Industrial Furnaces (BIF) checklists that have occurred through June 30, 1999:

- Revision Checklist 85 [56 FR 7134 (February 21, 1991)];
- Revision Checklist 94 [56 FR 32688 (July 17, 1991)];
- Revision Checklist 96 [56 FR 42504 (August 27, 1991)];
- Revision Checklist 98 [56 <u>FR</u> 43874 (September 5, 1991)];
- Revision Checklist 105 [57 FR 27880 (June 22, 1992)];
- Revision Checklist 110 [57 <u>FR</u> 37284 (August 18, 1992)];
- Revision Checklist 111 [57 FR 38558 (August 25, 1992)];
- Revision Checklist 114 [57 <u>FR</u> 44999 (September 30, 1992)];
- Revision Checklist 125 [58 FR 38816 (July 20, 1993)];
- Revision Checklist 127 [58 <u>FR</u> 59598 (November 9, 1993)];
- Revision Checklist 164 [63 <u>FR</u> 18504 (April 15, 1998)]; and
- Revision Checklist 169 [63 <u>FR</u> 42110 (August 6, 1998), 63 <u>FR</u> 54356 (October 9, 1998)].

Note that Revision Checklists 105 and 110, which address Coke By-Products, are included in this consolidated checklist because they also affect the BIF rules.

This Consolidated Checklist also includes changes to part 266 made by the Universal Treatment Standards Rule addressed by Revision Checklist 137 (59 FR 47982, September 19, 1994; 60 FR 242, January 3, 1995). This Land Disposal Restriction rule conditionally exempts mercury recovery furnaces and certain mercury-bearing hazardous wastes from the BIF rules. Revision Checklist 137 revised 266.100(c)(1), 266.100(c)(3), 266.100(c)(3)(i), 266.100(c)(3)(i), and 266.100(c)(3)(ii), and added Appendix XIII to part 266. While Revision Checklist 137 is not a BIF checklist, its revisions, as they relate to the BIF rules, are noted in the checklist column of this consolidated checklist.

On June 29, 1995, EPA published a final rule removing provisions from the Code of Federal Regulations that are no longer legally in effect (see Revision Checklist 144; 60 <u>FR</u> 33912). While Revision Checklist 144 is not a BIF checklist, it is noted in the checklist column of this consolidated BIF checklist because of the revisions it made to \$266.103(c)(5) and \$266.104(f).

- 2) Note that the regulations addressed by this checklist typically do not make a distinction between the various types of burning devices. However, the provisions in the regulations as they apply to sludge dryers, carbon regeneration units, infrared incinerators, and plasma arc incinerators are considered to be non-HSWA requirements, while the regulations as they apply to all other types of burning devices are HSWA provisions. EPA will implement the HSWA requirements in authorized States until the States modify their programs and such modifications are approved by EPA. The non-HSWA requirements are applicable only in those States which are unauthorized. In authorized States, the non-HSWA requirements will not be applicable until the States revise their programs to adopt equivalent requirements under State law.
- 3) Revision Checklist 98 addresses an administrative stay of the permitting standards for BIFs adopted pursuant to the February 21, 1991 (56 FR 7134; Revision Checklist 85) final rule as it applies to coke ovens burning certain

hazardous wastes from the coke by-products recovery process. This administrative stay has been removed by Revision Checklist 105 (57 FR 27880; June 22, 1992) and therefore, should not be adopted by States.

4) The final rule addressed by Revision Checklist 125 was promulgated pursuant to the Clean Air Act, rather than the Resource Conservation and Recovery Act, and primarily amends regulations in 40 CFR Parts 51 and 52. However, this rule also makes conforming changes to 40 CFR Parts 260 and 266 to ensure that the guidelines for air quality modeling and screening for boilers and industrial furnaces burning hazardous waste are consistent with the guidelines in 40 CFR Part 51. Only the changes to 40 CFR Parts 260 and 266 are included in Revision Checklist 125 and in this consolidated checklist. These revisions are necessary. Therefore, Revision Checklist 125 has been developed to help States maintain consistency with the Federal regulations. Note that States do not have to adopt the changes to 40 CFR Parts 51 and 52 to make the Part 260 and 266 changes. Rather, States should reference Appendix W, Part 51 at 266.104(e)(3) and 266.106(h).

Note that EPA's Office of Solid Waste is treating the changes made by the Air rule to 40 CFR Parts 260 and 266 as HSWA provisions because they amend the BIF regulations promulgated under HSWA.

5) Although Revision Checklist 127 is designated as optional, EPA strongly recommends that States adopt the less stringent requirements of this administrative stay because the nonmetal limits affected by the stay are extremely conservative and were based on unintended mistaken assumptions. This rule replaces the current nonmetal limits needed to qualify for the Bevill exemption, as specified in the February 21, 1991 rule (Revision Checklist 85), with the land disposal restriction (LDR) limits for underlying constituents in nonwastewaters pending further administrative action to establish appropriate health-based levels.

Note that the administrative stay is conditioned on compliance with the interim LDR exemption values. Noncompliance with those values would mean that the owner or operator of the Bevill device is no longer meeting the conditions of the administrative stay and, therefore, must comply with the comparison test in  $\S$  266.112(b)(1), in order to qualify for the exclusion in  $\S$  266.112. If the owner or operator meets neither the conditions of the stay nor the comparison test, then the residue would be subject to regulation as hazardous waste. Additionally, the stay does not affect the application of the procedural requirements in 266.112(b)(2) except as outlined in 58  $\overline{FR}$  59600, column 3, sections V. A-D.

						STATE AN	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	PART 260 - H	IAZARDOUS	WASTE MANAGE	MENT SYST	EM: GE	ENERAL		
	SUBPART B - DEFINITIONS							
	DEFINITIONS							
†	change "Parts 260 through 265 and 268" to "Parts 260 through 266 and 268"; remove "266, 268, and 270 through"	85, 175	260.10(intro)					
	"carbon regeneration unit"	85	260.10					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	_
			ANALOGOUS		LESS	MORE	BROADE
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	STATE CITATION	EQUIV- ALENT	STRIN- GENT	STRIN- GENT	R IN SCOPE
revise "incinerator"	85	260.10(1)&(2)					
replace "controlled flame devices" with "thermal treatment" in introductory text of the definition for "industrial furnace"	85	260.10					
redesignate paragraph (12) in the definition for "industrial furnace" as paragraph (13); add new paragraph (12) that adds halogen acid furnaces to the list of devices considered industrial furnaces	85	260.10(12)&(13)					
"infrared incinerator"	85,111	260.10					
"plasma arc incinerator"	85,111	260.10					
"sludge dryer"	85	260.10					
REFERENCES							
add to first set of listings in alphabetical order a reference to the October 1992 version of "U.S. EPA, Screening Procedures for Estimating the Air Quality Impact of Stationary Sources"	85,125	260.11(a)					
	SUBPART	C - RULEMAKINO	FETITIONS				
GENERAL	~						
replace "265" with "266" in the first sentence	111	260.20(a)					

Page 3 of 115

dcbif99.rtf - Revised: 9/23/99

	Done	and middsu	iai i umaces as or jun	c 30, 1777 (cc	iii u)			
						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	PART 261 - I	IDENTIFICA'	TION AND LISTING	G OF HAZAF	RDOUS V	WASTE		
		S	UBPART A - GENE	RAL				
	DEFINITION OF SOLID WAS	STE						
1	redesignate (d)(2) as (d)(3); add new paragraph regarding secondary materials fed to a halogen acid furnace that exhibit a characteristic or are a listed waste; exception for brominated material that meets certain criteria	85, 94,96	261.2(d)(2)					
	material must contain a bromine concentration of at least 45%	96	261.2(d)(2)(i)					
	material must contain less than a total of 1% of toxic organic compounds listed in Appendix VIII	96	261.2(d)(2)(ii)					
	material is processed continually on-site in the halogen acid furnace via direct conveyance	96	261.2(d)(2)(iii)					
	redesignate old 261.2(d)(2) as 261.2(d)(3)	85,94	261.2(d)(3)					

dcbif99.rtf - Revised: 9/23/99

Printed: 11/19/99

261.2(e)(2)(iv)

111

change "paragraph" to "paragraphs"; insert "and (d)

(2)" after "(d)(1)"

						STATE AN	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	DEFINITION OF HAZARDO	US WASTE						
†	insert ", provided that the wastesseparation" after "§ 261.32"; insert "crude oil storage tank sediment (EPA Hazardous Waste No. K172)" after "(EPA Hazardous Waste No. K050)"	169	261.3(a)(2)(iv)(C)					
2, 3,†	replace "261.6(a)(3)(v) through (ix)" with "261.6(a)(3)(v) through (viii)"; replace "\$ 261.6(a)(3)(iv) through (vi) "with "\$ 261.6(a)(3)(iii) and (iv)"	94,96,169	261.3(c)(2)(ii)(B)					
†	add subparagraph; catalyst inert support media separated from wastes listed in § 261.32 – Spent hydrotreating catalyst and spent hydrorefining catalyst	169	261.3(c)(2)(ii)(E)					
	EXCLUSIONS							
†	add exclusion for K060, K087, K141, K142, K143, K144, K145, K147, K148 and other wastes from coke by-products that are hazardous only because they exhibit the Toxicity Characteristic when recycled as specified; exclusion is conditioned on there being no land disposal of the wastes from point of generation to recycling point	85, †105,110	261.4(a)(10)					

dcbif99.rtf - Revised: 9/23/99

					STATE ANA		
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
† add exclusion; condensates derived from overhead gases from kraft mill steam strippers used to comply with 40 CFR 63.446(e); exemption applies only to combustion at mills generating condensates	164	261.4(a)(15)					
insert "except as provided by §266.112 of this chapter for facilities that burn or process hazardous waste" at end of paragraph	85	261.4(b)(4)					
revise first sentence to include phosphate rock and overburden from the mining of uranium ore in the existing parenthetical phrase; insert "except as provided by §266.112 of this chapter for facilities that burn or process hazardous waste" at end of first sentence	85	261.4(b)(7)					
add "except as provided by §266.112 of this chapter for facilities that burn or process hazardous waste" to end of paragraph	85	261.4(b)(8)					
REQUIREMENTS FOR REC	YCLABLE M.	ATERIALS	_				
replace the letter "G" with "H"	94	261.6(a)(2)					
replace "Subpart D" with "Subpart H"	94	261.6(a)(2)(ii)					
remove existing paragraph 261.6(a)(3)(vii) and redesignate 261.6(a)(3)(viii) as 261.6(a)(3)(viii)	85	261.6(a)(3)(vii)					

dcbif99.rtf - Revised: 9/23/99

#### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

					STATE AN	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
redesignate 261.6(a)(3)(ix) as 261.6(a)(3)(viii)	85	261.6(a)(3)(viii)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
S	SUBPART D -	LISTS OF HAZAR	DOUS WAS	ΓES			
HAZARDOUS WASTES FRO	M SPECIFIC	SOURCES					
add K141-K145, K147 and K148 in alphanumeric order to the subgroup "Coking" as specified at 57 FR 37305; add following waste streams to subgroup "Petroleum refining", in alphanumeric order	110,169	261.32					
Industry and EPA hazardous waste No.	Haza	ardous Waste				Hazard code	
K172 Spent Hydrorefinin	tank sediment and g catalyst from p s to other catalyting catalyst from p	d/or in-line filter/separationetroleum refining operation creactors (this listing does	on solids from pet ons, including gua es not include ine ons, including gua	roleum refi	ining ed to media). ed to		
	APP	PENDIX VII TO PAI	RT 261				
BASIS FOR LISTING HAZAF	RDOUS WAS	ТЕ					
add K141-K145, K147 and K148 in alphanumeric order as specified at 57 FR 37305; add to appendix in alphanumeric order, the following waste streams to subgroup "Petroleum refining"	110, 169	261 Appendix VII					
EPA hazardous waste No.	Hazardous cons	stituents for which listed					
K169 Benzene. K170 Benzo(a)pyrene, d benzo(k)fluoranthene, 3-methylcholant K171 Benzene, arsenic. K172 Benzene, arsenic.			benzo(b)fluorantl	nene,			

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

					STATE A	NALOG IS:				
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE			
PART 264 - STANDA TRE		WNERS AND OPE ORAGE, AND DIS			DOUS V	WASTE				
	SU	JBPART A - GENE	RAL							
PURPOSE, SCOPE, AND API	PLICABILITY	Y								
change "subparts C, D, F, or G" to "subparts C, F, G, or H"	111	264.1(g)(2)								
	SUBPART G	- CLOSURE AND P	OST-CLOSU	IRE						
CLOSURE OF PLAN; AMEN	DMENT OF I	PLAN								
add sentence regarding written notification of Regional Administrator at least 45 days prior to partial or final closure of a boiler or industrial furnace	85	264.112(d)(1)								
	SUBI	PART O - INCINER	ATORS							
APPLICABILITY										
regulations apply to owners and operators of hazardous waste incinerators (as defined in 260.10) except as 264.1 provides otherwise	85	264.340(a)								
PART 265 - INTER HAZARDOUS V		STANDARDS FOR ATMENT, STORAG								
	SU	JBPART A - GENE	RAL							
PURPOSE, SCOPE, AND APPLICABILITY										
change "subparts C, D, F, or G" to "subparts C, F, G, or H"	111	265.1(c)(6)								
SUBPART G - CLOSURE AND POST-CLOSURE										
CLOSURE PLAN; AMENDM	ENT OF PLA	N								

Page 9 of 115

dcbif99.rtf - Revised: 9/23/99

					STATE ANALOG IS:		
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
insert "or by six months after the effective date of the rule that first subjects a facility to provisions of this section" after "By May 19, 1981"	85	265.112(a)					
add sentence regarding submittal of closure plan at least 45 days prior to beginning partial or final closure of a boiler or industrial furnace; add sentence regarding written notification at least 45 days prior to beginning partial or final closure of a boiler or industrial furnace when the owner or operator has an approved closure plan	85	265.112(d)(1)					
date when owner or operator "expects to begin closure" must be either:	85,96	265.112(d)(2)					
compliance dates for hazardous waste units receiving final or most recent volume of hazardous wastes; extension by Regional Administrator, or	85,96	265.112(d)(2)(i)					
compliance dates for hazardous waste units meeting 265.113(d) requirements receiving final volume or most recent volume nonhazardous wastes; extension by Regional Administrator	85,96	265.112(d)(2)(ii)					

Page 10 of 115

CLOSURE; TIME ALLOWED FOR CLOSURE

dcbif99.rtf - Revised: 9/23/99

٠						STATE A	NALOG IS:	_
,	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	within 90 days after receiving final volume of hazardous or non-hazardous wastes if owner/operator complies with 265.113(d)&(e) requirements or 90 days after approval of closure plan, whichever is later; criteria for extension by Regional Administrator	85,96	265.113(a)					
4	complete partial and final closure within 180 days after receiving final volume of hazardous or non-hazardous waste if owner/operator complies with 265.113(d)&(e) requirements or 180 days after approval of closure plan, whichever is later; extension by Regional Administrator	85,96	265.113(b)					
		SUBF	PART O - INCINER	ATORS				
	APPLICABILITY							
	regulations apply to owners and operators of hazardous waste incinerators (as defined in 260.10) except as 264.1 provides otherwise	85	265.340(a)					
		SUBPAR	ΓP - THERMAL TR	REATMENT				
į	OTHER THERMAL TREATM	IENT					1	
	delete "." at the end and insert ", and Subpart H of Part 266, if the unit is a boiler or an industrial furnace as defined in \$260.10."	94	265.370					

SUBPART D - HAZARDOUS WASTE BURNED FOR ENERGY RECOVERY

AND SPECIFIC TYPES OF HAZARDOUS WASTE MANAGEMENT FACILITIES

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

#### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

						STATE AN	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	remove and reserve Subpart D	85	266.30-266.35					
5	SUBPAI	RT E - USED	OIL BURNED FOR	ENERGY R	ECOVE	RY	-	•
	APPLICABILITY							
6	replace "Subpart D of Part 266" with "Subpart H of Part 266"	94,96	266.40(c)					
6	replace "Subpart D" with "Subpart H"	94,96	266.40(d)					

dcbif99.rtf - Revised: 9/23/99

						STATE AN	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	SUBPART H - HAZARI	DOUS WAST	E BURNED IN BOI	LERS AND I	NDUST	RIAL FU	JRNAC	ES
	APPLICABILITY							
7	regulations apply to hazardous waste burned or processed in a boiler or industrial furnace, irrespective of purpose, except as 266.100(b),(c),(d) and (f) provide; definition of "burn"; 266.104-266.107 emissions standards apply to interim status or permitted facilities	85,96,†98, †105,111	266.100(a)					
	hazardous wastes and facilities not subject to regulation under Subpart H:	85	266.100(b)					
8	used oil burned for energy recovery that is hazardous solely because it exhibits a characteristic; regulated under 266, Subpart E	85	266.100(b)(1)					
	gas recovered from landfills and burned for energy recovery	85,94	266.100(b)(2)					
3,9, 10, †	exempt hazardous wastes under 261.4 and 261.6(a)(3) (iii) and (iv); CESQG hazardous wastes under 261.5	85,94, 169	266.100(b)(3)					
	coke ovens burning only K087	85	266.100(b)(4)					
	owners and operators of smelting, melting and refining furnaces processing hazardous waste solely for metal recovery conditionally exempt, except for 266.101 and 266.112	85	266.100(c)					

Page 13 of 115

dcbif99.rtf - Revised: 9/23/99

						STATE AN	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
11	requirements for exemption from 266.102 through 266.111 for owner or operator of metal recovery furnace or mercury recovery furnace; owner or operator of a lead or a nickel-chromium recovery furnace, or certain metal recovery furnaces subject to 266.100(c) (3) requirements	85,96,137	266.100(c)(1)					
	one-time written notice indicating:	85	266.100(c)(1)(i)					
	owner or operator claims 266.100(c) exemption	85	266.100(c)(1)(i) (A)					
	metal recovery as per 266.100(c)(2) provisions	85	266.100(c)(1)(i)(B)					
	recoverable levels of metals	85	266.100(c)(1)(i)(C)					
	compliance with 266.100(c) sampling and analysis and recordkeeping requirements	85	266.100(c)(1)(i) (D)					
	sample and analyze hazardous waste and other feedstocks as necessary using specified procedures or alternative methods that meet or exceed SW-846 method performance capabilities; situation where "best available method" is used	85,96	266.100(c)(1)(ii)					
	maintain specified records at facility for at least three years	85	266.100(c)(1)(iii)					
	criteria under which a hazardous waste is not processed solely for metal recovery	85	266.100(c)(2)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
total concentration of 261, Appendix VIII organic compounds exceeds 500 ppm by weight and are considered burned for destruction; reduction of organic compound concentration to the 500 ppm limit by bona fide treatment; blending for dilution to meet the 500 ppm limit is prohibited; retention of documentation in records required by 266.100(c) (1)(iii)	85,96	266.100(c)(2)(i)					
heating value of 5,000 Btu/lb or more and considered burned as fuel; reduction of the heating value to below 5,000 Btu/lb by bona fide treatment; blending for dilution to meet the 5,000 Btu/lb limit is prohibited; retention of documentation in records required by 266.100(c)(1)(iii)	85,96	266.100(c)(2)(ii)					
11 requirements for exemption from 266.102 through 266.111 for owner or operator of certain metal recovery furnaces; written notice to director; 266.100(c)(1) compliance	96,137	266.100(c)(3)					
11 exemption from 266.100(c)(1) requirements for hazardous wastes listed in Appendices XI, XII, and XIII, Part 266, and baghouse bags used to capture metallic dusts emitted by steel manufacturing, provided:	96,137	266.100(c)(3)(i)					

dcbif99.rtf - Revised: 9/23/99

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
11	waste contains recoverable levels of specified metals	96,137	266.100(c)(3)(i) (A)					
	waste does not exhibit the Toxicity Characteristic of 261.24 for an organic constituent	96	266.100(c)(3)(i)(B)					
	waste is not a hazardous waste listed in Part 261 Subpart D because it is listed for an organic constituent as identified in Appendix VII of Part 261	96	266.100(c)(3)(i)(C)					
	certification by owner or operator under 266.100(c)(3) regarding hazardous waste; sampling and analysis or other information to assure compliance; sampling and analysis conducted according to 266.100(c)(1)(ii); maintain records to document compliance with (c)(3) for at least three years	96	266.100(c)(3)(i) (D)					
11	basis for case-by-case decisions regarding toxic organic constituents; metal recovery furnace subject to Subpart H requirements after adequate notice and opportunity for comment; factors Director will consider:	96,137	266.100(c)(3)(ii)					
	concentration and toxicity of organic constituents in the material	96	266.100(c)(3)(ii) (A)					
	level of destruction of toxic constituents provided by the furnace	96	266.100(c)(3)(ii) (B)					

dcbif99.rtf - Revised: 9/23/99

	<u> </u>				STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
acceptable ambient levels established in Appendices IV or V, Part 266, exceeded for any toxic organic compound that may be emitted based on certain conditions	96	266.100(c)(3)(ii) (C)					
266.111 direct transfer operation standards apply only to facilities subject to 266.102 or 266.103 standards	85	266.100(d)					
266.112 residue management standards apply to any boiler or industrial furnace burning hazardous waste	85	266.100(e)					
conditional exemption from Subpart H requirements for owners or operators of certain smelting, melting, and refining furnaces, except for 266.112; to be exempt from 266.101 through 266.111, an owner or operator must:	96,111	266.100(f)					
provide a one-time written notice indicating:	96	266.100(f)(1)					
owner or operator claims 266.100(f) exemption	96	266.100(f)(1)(i)					
hazardous waste is burned for legitimate recovery of precious metal	96	266.100(f)(1)(ii)					
compliance with 266.100(f) sampling and analysis and recordkeeping requirements	96	266.100(f)(1)(iii)					
sample and analyze hazardous waste as necessary using specified procedures	96	266.100(f)(2)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
maintain specified records at facility for at least three years	96	266.100(f)(3)					
MANAGEMENT PRIOR TO	BURNING						
generators of hazardous waste that is burned in a boiler or industrial furnace subject to Part 262	85	266.101(a)					
transporters of hazardous waste that is burned in a boiler or industrial furnace subject to Part 263	85	266.101(b)					
owners and operators of facilities that store hazardous waste burned in a boiler or industrial furnace subject to the applicable provisions of parts 264, 265, and 270, except as provided by 266.101(c)(2); standards applicable to storage by burners and intermediary facilities	85,111	266.101(c)(1)					
generators of hazardous waste who burn on-site in boilers or industrial furnaces exempt from regulation under 266.108 small quantity burner provisions are exempt from the regulations of parts 264, 265, and 270 applicable to storage units for those storage units that store mixtures of hazardous waste and the primary fuel in tanks that feed mixture directly to burner; hazardous waste storage prior to mixing subject to 266.101(c) (1) regulation	85,111	266.101(c)(2)					

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

#### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
PERMIT STANDARDS FOR	BURNERS						
owners and operators not operating under interim status and not exempt under 266.108 small quantity burner exemption are subject to 266.102, 270.22 and 270.66 requirements	85	266.102(a)(1)					
		266.102(a)(2)					
		266.102(a)(2)(i)					
		266.102(a)(2)(ii)					
		266.102(a)(2)(iii)					
		266.102(a)(2)(iv)					
		266.102(a)(2) (v)					
		266.102(a)(2)(vi)					
		266.102(a)(2)(vii)					
		266.102(a)(2)(viii)					
applicable 264 provisions	85	266.102(a)(2)(ix)					

dcbif99.rtf - Revised: 9/23/99

					STATE ANALOG IS:		
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
analysis to quantify concentration of any 261, Appendix VIII constituent at levels detectable by specified analytical procedures, alternative methods or best available method; identification; explanation of constituents excluded from analysis; analysis provides 266 Subpart H, 270.22 and 270.66 information to prescribe permit conditions; analysis included in Part B permit application or in trial burn plan for interim status facilities; owners/ operators of units not operating under interim status include 270.22 or 270.66(c) information in Part B application, to extent possible	85, 94,96	266.102(b)(1)					
sampling and analysis throughout normal operation to ensure permit-specified physical and chemical composition limits are met	85	266.102(b)(2)					
compliance with 266.104 through 266.107 emissions standards	85	266.102(c)					
burn only hazardous wastes specified in permit under 266.102(e) operating conditions; exception for approved trial burns under 270.66 conditions	85	266.102(d)(1)					

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

Page 20 of 115

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
new permit or permit modification necessary to burn hazardous waste not specified in permit; trial burn results or Part B alternative data form basis for new waste operating requirements	85	266.102(d)(2)					
266.103 interim status boilers and industrial furnaces permitted under 270.66(g) procedures	85	266.102(d)(3)					
permit for new boiler or industrial furnace must establish appropriate conditions for each applicable 266.102 requirement in order to comply with specified standards:	85	266.102(d)(4)					
for period beginning with initial introduction of hazardous waste and ending with initiation of trial burn; such period not to exceed 720 hours; operating requirements in compliance with 266.104-266.107 emissions standards; applicable provisions when seeking waiver from a trial burn; extension for up to 720 additional hours by Director based on good cause demonstration	85	266.102(d)(4)(i)					
during trial burn, operating requirements sufficient for 266.104-266.107 emissions compliance and in accordance with approved trial burn plan	85	266.102(d)(4)(ii)					

dcbif99.rtf - Revised: 9/23/99

				STATE AN  LESS EQUIV-STRIN- ALENT GENT	NALOG IS:		
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	-	STRIN-	MORE STRIN- GENT	BROADE R IN SCOPE
immediately after trial burn, for minimum period needed to allow sample analysis, data computation, submission and review of trial burn results, and permit modification, operating requirements to ensure 266.104-266.107 emissions compliance	85	266.102(d)(4)(iii)					
for duration of permit, operating requirements based on trial burn or 270.22 alternative data, sufficient to ensure 266.104-266.107 emissions compliance	85,94	266.102(d)(4)(iv)					
operating requirements specified in the permit apply at all times where hazardous waste is in unit	85	266.102(e)(1)					
operating conditions, either case-by-case for each hazardous waste to ensure compliance with 266.104(a) DRE performance standard or special operating requirements provided by 266.104(a)(4) DRE trial burn waiver; when no waiver, each set of operating requirements will specify composition of hazardous waste to which they apply; permit-specified operating limits for each hazardous waste include:	85	266.102(e)(2)(i)					
feed rate of hazardous waste	0.3	200.102(e)(2)(1)					
and other fuels as per 266.102(e)(6)	85	266.102(e)(2)(i) (A)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
minimum and maximum device production rate when producing normal product as per 266.102(e)(6)	85	266.102(e)(2)(i)(B)					
appropriate controls of hazardous waste firing system	85	266.102(e)(2)(i)(C)					
allowable variation in boiler and industrial furnace system design or operating procedures	85	266.102(e)(2)(i) (D)					
minimum combustion gas temperature measured at a location indicative of combustion chamber temperature as per 266.102(e) (6)	85	266.102(e)(2)(i)(E)					
appropriate indicator of combustion gas velocity as per 266.102(e)(6), unless 270.66 documentation	85	266.102(e)(2)(i)(F)					
other operating requirements to ensure 266.104(a) DRE compliance	85	266.102(e)(2)(i)(G)					
permit must incorporate carbon monoxide (CO) limit and, as appropriate, hydrocarbon (HC) limit as per 266.104(b)-(f); permit limits specified:	85	266.102(e)(2)(ii)					
when complying with 266.104(b)(1) CO standard, permit limit is 100 ppmv	85	266.102(e)(2)(ii) (A)					

dcbif99.rtf - Revised: 9/23/99

					STATE ANALOG IS:		
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
when complying with 266.104(c) alternative CO standard, permit limit based on trial burn, established as specified average, and permit limit for HC is 20 ppmv, except as 266.104(f) provides	85	266.102(e)(2)(ii) (B)					
when complying with 266.104(f) alternative HC limit, permit limit for HC and CO is baseline level when hazardous waste is not burned	85	266.102(e)(2)(ii) (C)					
no hazardous waste as feed during start-up and shut-down, unless device is operating within permit conditions; exception	85	266.102(e)(2)(iii)					
except as provided in 266.102(e)(3)(ii) and (iii), operating requirements the permit will specify to ensure 266.105 particulate standard compliance:	85	266.102(e)(3)(i)					
total ash feed rate from hazardous waste, other fuels, and industrial furnace feedstocks, as per 266.102(e) (6)	85	266.102(e)(3)(i) (A)					
maximum device production rate when producing normal product as per 266.102(e)(6)	85	266.102(e)(3)(i)(B)					
operation and maintenance controls for hazardous waste firing system and air pollution control system	85	266.102(e)(3)(i)(C)					

dcbif99.rtf - Revised: 9/23/99

Page 24 of 115 Printed: 11/19/99

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	allowable variation in system design including air pollution control system or operating procedures	85	266.102(e)(3)(i) (D)					
13	other operating requirements to ensure 266.111(b) particulate standard compliance	85	266.102(e)(3)(i)(E)					
	no permit conditions to ensure particulate standard compliance for 266.105(b) exempt facilities	85	266.102(e)(3)(ii)					
	for cement kilns and light- weight aggregate kilns, permit conditions shall not limit ash content of hazardous waste or other feed materials	85	266.102(e)(3)(iii)					
	operating requirements the permit will specify to conform with 266.106(b) or (e) Tier I or adjusted Tier I metals feed rate screening limits:	85	266.102(e)(4)(i)					
	total feed rate of each metal in hazardous waste, other fuels, and industrial furnace feedstocks as per 266.102(e) (6)	85	266.102(e)(4)(i) (A)					
	total feed rate of hazardous waste as per 266.102(e)(6)	85	266.102(e)(4)(i)(B)					
	sampling and metals analysis program	85,94	266.102(e)(4)(i)(C)					

dcbif99.rtf - Revised: 9/23/99

#### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

				STATE ANALOG IS:			
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
operating requirements the permit will specify to conform with 266.106(c) Tier II metals emission rate screening limits and 266.106(d) Tier III metals controls:	85	266.102(e)(4)(ii)					
maximum emission rate for each metal based on average rate during trial burn	85	266.102(e)(4)(ii) (A)					
feed rate of total and pumpable hazardous waste as per 266.102(e)(6)(i)	85	266.102(e)(4)(ii) (B)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
4	85	266.102(e)(4)(ii) (C)					
		266.102(e)(4)(ii) (C)(1)					
feed rate of each metal in		266.102(e)(4)(ii) (C)(2)					
specified feedstreams, measured and specified as 266.102(e)(6)	per 85,96	266.102(e)(4)(ii) (C)(3)					
total feed rate of chlorine a chloride in total feedstream as per 266.102(e)(6)		266.102(e)(4)(ii) (D)					
maximum combustion gas temperature measured at location indicative of combustion chamber temperature as per 266.102 (6)	e(e) 85	266.102(e)(4)(ii) (E)					
maximum flue gas temperature at inlet to particulate matter air polluti control system as per 266.102(e)(6)	on 85	266.102(e)(4)(ii) (F)					
maximum device production rate when producing normal product as per 266.102(e)(6	ıl	266.102(e)(4)(ii) (G)					
operation and maintenance controls of hazardous waste firing system and any air pollution control system	85	266.102(e)(4)(ii) (H)					
allowable variation in system design including air pollution control system or operating procedures	ı	266.102(e)(4)(ii)(I)					

dcbif99.rtf - Revised: 9/23/99

						STATE A	NALOG IS:		
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE	
	other operating requirements to ensure 266.106(c) or (d) metals standards compliance	85	266.102(e)(4)(ii)(J)						
	operating requirements the permit will specify to conform with 266.106(f) alternative implementation approach:	85	266.102(e)(4)(iii)						
	maximum emission rate for each metal based on average rate	85	266.102(e)(4)(iii) (A)						
	feed rate of total and pumpable hazardous waste as per 266.102(e)(6)(i)	85	266.102(e)(4)(iii) (B)						
14, 15		85	266.102(e)(4)(iii) (C)						
	feed rate of each metal in specified feedstreams,		266.102(e)(4)(iii) (C)(1)						
	measured and specified as per 266.102(e)(6)	85,96	266.102(e)(4)(iii) (C)(2)						
	total feed rate of chlorine and chloride in total feedstreams as per 266.102(e)(6)	85	266.102(e)(4)(iii) (D)						
	maximum combustion gas temperature measured at location indicative of combustion chamber temperature as per 266.102(e) (6)	85	266.102(e)(4)(iii) (E)						
	maximum flue gas temperature at inlet to particulate matter air pollution control system as per 266.102(e)(6)	85	266.102(e)(4)(iii) (F)						

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

Page 28 of 115

Control of the Print Rev

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
maximum device production rate when producing normal product as per 266.102(e)(6)	85	266.102(e)(4)(iii) (G)					
operation and maintenance controls of hazardous waste firing system and any air pollution control system	85	266.102(e)(4)(iii) (H)					
allowable variation in system design including air pollution control system or operating procedures	85	266.102(e)(4)(iii) (I)					
other operating requirements to ensure 266.106(c) or (d) metals standards compliance	85	266.102(e)(4)(iii) (J)					
operating requirements the permit will specify to ensure 266.107(b)(1) Tier I total chloride and chlorine feed rate screening limits conformance:	85	266.102(e)(5)(i)					
feed rate of total chloride and chlorine in hazardous waste, other fuels, and industrial furnace feedstocks as per 266.102(e)(6)	85	266.102(e)(5)(i) (A)					
feed rate of total hazardous waste as per 266.102(e)(6)	85	266.102(e)(5)(i)(B)					
sampling and analysis program for total chloride and chlorine	85	266.102(e)(5)(i)(C)					
operating requirements the permit will specify for 266.107(b)(2) Tier II and 266.107(c) Tier III HCl and Cl <sub>2</sub> emission rate screening limits conformance:	85	266.102(e)(5)(ii)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
maximum emission rate for HCl and Cl <sub>2</sub> based on average rate	85	266.102(e)(5)(ii) (A)					
feed rate of total hazardous waste as per 266.102(e)(6)	85	266.102(e)(5)(ii) (B)					
total feed rate of chlorine and chloride in total feedstreams as per 266.102(e)(6)	85	266.102(e)(5)(ii) (C)					
maximum device production rate when producing normal product as per 266.102(e)(6)	85	266.102(e)(5)(ii) (D)					
operation and maintenance controls of hazardous waste firing system and any air pollution control system	85	266.102(e)(5)(ii) (E)					
allowable variation in system design including air pollution control system or operating procedures	85	266.102(e)(5)(ii) (F)					
other operating requirements to ensure 266.107(b)(2) or (c) HCl or Cl <sub>2</sub> standards compliance	85	266.102(e)(5)(ii) (G)					
measuring parameters and establishing limits based on trial burn data	85,94	266.102(e)(6)					
as specified in 266.102(e)(2)-(5), each operating parameter shall be measured and permit limits on the parameter established according to either of following procedures:	85	266.102(e)(6)(i)					
measured and recorded on instantaneous basis and permit limit based on time-weighted average	85	266.102(e)(6)(i) (A)					

dcbif99.rtf - Revised: 9/23/99

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
			266.102(e)(6)(i)(B) (1)					
		85	266.102(e)(6)(i)(B) (1)(i)					
	hourly rolling average basis as defined	85,94	266.102(e)(6)(i)(B) (1)(ii)					
16	permit limit based on average over all valid test runs of highest hourly rolling average value per run	85,94	266.102(e)(6)(i)(B) (2)					
	feed rate limits for carcinogenic metals and lead established on either an hourly rolling average basis or on (up to) 24-hour rolling average basis; requirements for 2- to 24-hour average period:	85,94	266.102(e)(6)(ii)					
	feed rate of each metal limited to ten times the allowable hourly rolling average basis feed rate	85	266.102(e)(6)(ii) (A)					
16			266.102(e)(6)(ii) (B)					
		85	266.102(e)(6)(ii) (B)( <i>I</i> )					
	specifications the continuous monitor shall meet	85,94	266.102(e)(6)(ii) (B)(2)					
	feed rate permit limit based on specified average	85	266.102(e)(6)(ii) (C)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
feed rate limits for metals, total chloride and chlorine, and ash established and monitored based on feedstream concentration and flow rate; flow rate continuously monitored as per 266.102(e) (6)(i) and (ii)	85	266.102(e)(6)(iii)					
if no simultaneous demonstration of 266.104-266.107 compliance during a set of test runs, operating conditions of additional test runs as close as possible to original operating conditions	85	266.102(e)(6)(iv) (A)					
facility to operate under trial burn conditions and reach steady-state operations before obtaining test data to demonstrate 266.104-266.107 emissions standards compliance or establishing operating parameter limits; specific industrial furnaces need not reach steady-state conditions for flow of metals prior to beginning metals emissions compliance testing	85,94	266.102(e)(6)(iv) (B)					
trial burn data obtained during emissions sampling are used to establish operating parameter limits in the permit when parameter must be established as per 266.102(e)	85	266.102(e)(6)(iv) (C)					
requirements for controlling fugitive emissions	85	266.102(e)(7)(i) 266.102(e)(7)(i) (A)					
		266.102(e)(7)(i)(B)					

dcbif99.rtf - Revised: 9/23/99

-					am. m		
				-		NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
		266.102(e)(7)(i)(C)					
automatic waste feed cutoff required; Director may limit number of cutoffs per operating period; additional requirements include:	85	266.102(e)(7)(ii)					
maintenance of permit limit for minimum combustion chamber temperature while hazardous waste or residues remain in chamber	85	266.102(e)(7)(ii) (A)					
exhaust gases ducted to air pollution control system while hazardous waste or residues remain in chamber	85	266.102(e)(7)(ii) (B)					
continued monitoring of parameters with limits during cutoff and hazardous waste feed not restarted until parameters comply with limits; for parameters monitored on instantaneous basis, conditions for restarting hazardous waste feed	85	266.102(e)(7)(ii) (C)					
cease burning hazardous waste when changes in combustion properties, feed rates, or design or operating conditions deviate from permit limits	85	266.102(e)(7)(iii)					
owner or operator, while burning hazardous waste, must monitor and record:	85	266.102(e)(8)(i)					
specified feed rates and composition of specified materials	85	266.102(e)(8)(i) (A)					

Page 33 of 115

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
CO, HC, and oxygen on a continuous basis as specified; monitors installed, operated and maintained as per 266, Appendix IX methods	85	266.102(e)(8)(i)(B)					
sampling and analysis as requested to verify that requirements established in permit achieve 266.104-266.107 standards	85	266.102(e)(8)(i) (C)					
monitors record data in permit limit units, unless permit allows otherwise	85	266.102(e)(8)(ii)					
daily visual inspection of boiler or industrial furnace and associated equipment when they contain hazardous waste	85	266.102(e)(8)(iii)					
test automatic feed cutoff system and associated alarms at least once every 7 days when hazardous waste is burned unless specified conditions are demonstrated; operational testing at least once every 30 days	85	266.102(e)(8)(iv)					
monitoring and inspection data recorded and placed in 264.73 operating record	85	266.102(e)(8)(v)					
compliance with 266.111 if direct transfer of hazardous waste to boiler or industrial furnace without use of storage unit	85	266.102(e)(9)					
all 266.102-required information and data in facility operating record until closure of the facility	85,96	266.102(e)(10)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
remove all hazardous waste and hazardous waste residues at closure	85	266.102(e)(11)					
INTERIM STATUS STANDA	RDS FOR BU	JRNERS	1	1		1	1
establish minimum national standards for owners and operators of existing boilers and industrial furnaces until permitted under 266.102(d) or closed	85	266.103(a)(1)(i)					
definition of "existing or in existence"; facility has commenced construction if all permits necessary to begin physical construction are obtained and either:	85,94	266.103(a)(1)(ii)					
continuous on-site, physical construction program has begun	85	266.103(a)(1)(ii) (A)					
contractual obligations cannot be canceled or modified without substantial loss and physical construction is to be completed within reasonable time	85	266.103(a)(1)(ii) (B)					
if boiler or industrial furnace at facility with permit or interim status, then compliance with 270.42 permit modification or 270.72 interim status changes	85	266.103(a)(1)(iii)					
266.103 requirements not applicable to hazardous waste and facilities exempt under 266.100(b) or 266.108	85	266.103(a)(2)					

Page 35 of 115

dcbif99.rtf - Revised: 9/23/99

#### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

					STATE ANALOG IS:			
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE	
F020-F023, F026 or F027 hazardous waste listed for dioxin and hazardous waste derived from these wastes may not be burned in interim status boiler or industrial furnace	85,96	266.103(a)(3)						

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
		266.103(a)(4)					
		266.103(a)(4)(i)					
		266.103(a)(4)(ii)					
		266.103(a)(4)(iii)					
		266.103(a)(4)(iv)					
		266.103(a)(4)(v)					
		266.103(a)(4)(vi)					
interim status owners and		266.103(a)(4)(vii)					
operators subject to specified 265 provisions:	85	266.103(a)(4)(viii)					
controls that apply to interim status industrial furnaces that feed hazardous waste for a purpose other than solely as an ingredient at any location other than the hot end or where fuels are normally fired:	85,96	266.103(a)(5)					
fed at location where temperatures are at least 1800E F	85	266.103(a)(5)(i) (A)					
determination and documentation in facility record of adequate oxygen	85	266.103(a)(5)(i)(B)					
for cement kiln systems, hazardous waste fed into kiln	85	266.103(a)(5)(i)(C)					
applicability of 266.104(c) or 266.103(c)(5) hydrocarbon controls	85,96	266.103(a)(5)(i) (D)					
criteria for burning hazardous waste for a purpose other than solely as an ingredient:	85	266.103(a)(5)(ii)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
total concentration of 261, Appendix VIII nonmetal compounds exceed 500 ppm by weight as fired and considered burned for destruction; reduction of the concentration of nonmetal compounds to the 500 ppm limit by bona fide treatment; blending for dilution to meet the 500 ppm limit prohibited; retention of documentation in facility record	85,96	266.103(a)(5)(ii) (A)					
heating value of 5,000 Btu/lb or more, as fired, and considered burned as fuel; reduction of the heating value of a waste as-generated to below 5,000 Btu/lb limit by bona fide treatment; blending to augment heating value to meet the 5,000 Btu/lb limit prohibited; retention of documentation in facility record	85,96	266.103(a)(5)(ii) (B)					
burning hazardous waste with heating value less than 5,000 Btu/lb prohibited; situation where 5,000 Btu/lb limit can be exceeded; exceptions:	85,96	266.103(a)(6)					
hazardous waste burned solely as an ingredient	96	266.103(a)(6)(i)					
hazardous waste burned for purposes of compliance testing for a total period of time not to exceed 720 hours	96	266.103(a)(6)(ii)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
waste burned if Director has documentation to show that, prior to August 21, 1991:	96	266.103(a)(6)(iii)					
boiler or industrial furnace operating under Part 265, Subpart O or P requirements	96	266.103(a)(6)(iii) (A)					
boiler or industrial furnace met 270.70 interim status eligibility requirements for Part 265, Subpart O or Subpart P	96	266.103(a)(6)(iii) (B)					
hazardous waste with a heating value less than 5,000 Btu/lb burned prior to August 21, 1991	96	266.103(a)(6)(iii) (C)					
such waste burned in halogen acid furnace if waste burned as an excluded ingredient under 261.2(e) prior to February 21, 1991 and documentation kept on file	96	266.103(a)(6)(iv)					
266.111 compliance if hazardous waste directly transferred from transport vehicle to boiler or industrial furnace without storage unit use	85	266.103(a)(7)					
August 21, 1991 submittal date for 266.103(b)(2) information; establish limits for 266.103(b) (3) parameters; certificate of precompliance; burning limited to 266.103(b)(3) conditions until 266.103(b)(8) revised certification of precompliance, or 266.103(c) certification of compliance, or permit is issued	85	266.103(b)(1)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
information to be submitted with certification of precompliance to support determination and compliance with operating parameter limits	85	266.103(b)(2)					
		266.103(b)(2)(i)					
		266.103(b)(2)(i) (A)					
		266.103(b)(2)(i)(B)					
		266.103(b)(2)(i)(C)					
		266.103(b)(2)(i) (D)					
general facility information	85	266.103(b)(2)(i)(E)					
except for facilities complying with Tier I or Adjusted Tier I feed rate screening limits provided by 266.106(b) or (e) and 266.107(b)(1) or (e), estimated uncontrolled emissions of particulate matter, each 266.106 metal, hydrogen chloride and chlorine, and following information to support determinations:	85,111	266.103(b)(2)(ii)					
feed rate of specified materials in each feedstream	85,94	266.103(b)(2)(ii) (A)					
estimated partitioning factor to combustion gas for 266.103(b) (2)(ii)(A) materials, basis for estimate, and estimate of partitioning to HCl and Cl <sub>2</sub> of total chloride and chlorine in feed materials; use best engineering judgment or 266, Appendix IX procedures	85,94	266.103(b)(2)(ii) (B)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
for industrial furnaces that recycle collected particulate matter and certify compliance with 266.103(c)(ii)(A) metals emissions standards, estimated enrichment factor for each metal, using best engineering judgment or specified 266, Appendix IX procedures	85	266.103(b)(2)(ii) (C)					
basis for best engineering judgment; 270.11(d) certification of determinations included in certification of precompliance	85,94	266.103(b)(2)(ii) (D)					
for facilities complying with Tier I or Adjusted Tier I feed rate screening limits, the feed rate of specified materials in each feed stream	85,111	266.103(b)(2)(iii)					
for facilities complying with Tier II or III emission limits for metals or HCl or Cl <sub>2</sub> , estimated controlled emissions rates of particulate matter, each 266.106 metal, HCl and Cl <sub>2</sub> , and following information to support determinations:	85,94	266.103(b)(2)(iv)					
estimated air pollution control system (APCS) removal efficiency for specified materials	85	266.103(b)(2)(iv) (A)					
use best engineering judgment or 266, Appendix IX procedures	85	266.103(b)(2)(iv) (B)					
basis for best engineering judgment in conformance with 266.103(b)(2)(ii)(D)	85	266.103(b)(2)(iv) (C)					

dcbif99.rtf - Revised: 9/23/99

### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
determination of allowable emissions rates for specified materials and information to support such determinations to include:	85	266.103(b)(2)(v)					
		266.103(b)(2)(v) (A)					
		266.103(b)(2)(v) (A)(1)					
		266.103(b)(2)(v) (A)(2)					
		266.103(b)(2)(v) (A)(3)					
	85	266.103(b)(2)(v) (A)(4)					
	85,94	266.103(b)(2)(v) (A)(5)					
		266.103(b)(2)(v) (A)(6)					
for all facilities:	85	266.103(b)(2)(v) (A)(7)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
		266.103(b)(2)(v) (B)					
		266.103(b)(2)(v) (B)(1)					
for owners or operators using Tier III site specific dispersion modeling to determine		266.103(b)(2)(v) (B)(2)					
266.106(d) or 266.107(c) allowable levels, or adjusted Tier I feed rate screening		266.103(b)(2)(v) (B)(3)					
limits under 266.106(e) or 266.107(e):	85	266.103(b)(2)(v) (B)(4)					
for facilities complying with Tier II or III emissions rate controls for metals or HCl and Cl <sub>2</sub> , comparison of 266.103(b) (2)(iv) estimated rates with 266.103(b)(2)(v) allowable rates	85,94	266.103(b)(2)(vi)					
for facilities complying with Tier I or adjusted Tier I feed rate screening limits for metals or total chloride and chlorine, comparison of actual feed rates determined under 266.103(b)(2)(iii) to Tier I allowable feed rates	85	266.103(b)(2)(vii)					
for industrial furnaces that feed hazardous waste for any purpose other than solely as an ingredient at any location other than product discharge end of device, documentation of 266.103(a)(5)(i)(A)-(C) compliance	85	266.103(b)(2)(viii)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
for industrial furnaces that recycle collected particulate matter back into the furnace and that will certify 266.103(c)		266.103(b)(2)(ix)					
(3)(ii)(A) metals emissions standards compliance,		266.103(b)(2)(ix) (A)					
applicable particulate matter standard and precompliance limit on metal concentration	85	266.103(b)(2)(ix) (B)					
establish limits on 266.103(b) (3)(i)-(v) parameters consistent with 266.103(b)(2) determinations and certify the facility will operate within the limits during interim status when there is hazardous waste in the unit until certain conditions are met	85	266.103(b)(3)					
feed rate of total hazardous waste and pumpable hazardous waste	85	266.103(b)(3)(i)					
	85,94	266.103(b)(3)(ii)					
	85	266.103(b)(3)(ii) (A)					
	85,111	266.103(b)(3)(ii) (B)					
feed rate of each metal in specified feedstreams	85	266.103(b)(3)(ii) (C)					
total feed rate of chlorine and chloride in total feedstreams	85	266.103(b)(3)(iii)					
total feed rate of ash in total feedstreams, except ash feed rate for cement kilns and light- weight aggregate kilns is not limited	85	266.103(b)(3)(iv)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
maximum production rate when producing normal product, unless complying with the Tier I or Adjusted Tier I feed rate screening limits for chlorine under 266.106(b)(1) or (e) and for all metals under 266.106(b) or (e), and uncontrolled particulate emissions do not exceed 266.105 standard	85,111	266.103(b)(3)(v)					
special operating requirements under 266, Appendix IX for furnaces that recycle collected particulate matter back into furnace and that certify compliance with metals emissions controls under 266.103(c)(3)(ii)(A)	85	266.103(b)(4)					
limits on 266.103(b)(3) parameters established and continuously monitoring under:	85	266.103(b)(5)(i)					
instantaneous limits	85,96	266.103(b)(5)(i) (A)					
5	85	266.103(b)(5)(i)(B)					
		266.103(b)(5)(i)(B) (1)					
hourly rolling average basis as defined	85,94	266.103(b)(5)(i)(B) (2)					
feed rate limits for carcinogenic metals and lead established on either an hourly rolling average basis or on (up to) 24-hour rolling average basis; requirements for 2- to 24-hour average period:	85	266.103(b)(5)(ii)					

dcbif99.rtf - Revised: 9/23/99

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	feed rate of each metal limited to ten times the allowable hourly rolling average basis feed rate	85	266.103(b)(5)(ii) (A)					
16		85	266.103(b)(5)(ii) (B)					
			266.103(b)(5)(ii) (B)(1)					
Ī	specifications the continuous monitor shall meet:	85,94	266.103(b)(5)(ii) (B)(2)					
	feed rate limits for metals, total chloride and chlorine, and ash established and monitored based on feedstream concentration and flow rate; flow rate continuously monitored as per 266.103(b) (5)(i) and (ii)	85	266.103(b)(5)(iii)					
	on or before August 21, 1991, owner or operator submits notice to major local newspaper and sends copy of notice to State and local government units; provide evidence of notice submittal for publication with certification of pre-compliance to Director; notice must bear specified title and include:	85,94	266.103(b)(6)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
		266.103(b)(6)(i)					
		266.103(b)(6)(ii)					
		266.103(b)(6)(iii)					
		266.103(b)(6)(iv)					
		266.103(b)(6)(v)					
		266.103(b)(6)(vi)					
	85	266.103(b)(6)(vii)					
		266.103(b)(6)(viii)					
		266.103(b)(6)(viii) (A)					
	85,96	266.103(b)(6)(viii) (B)					
information to include in public		266.103(b)(6)(ix)					
notice	85	266.103(b)(6)(x)					
when monitoring systems for 266.103(c)(1)(v)-(xiii) operating parameters are installed and operating in conformance with vendor or 266, Appendix IX specifications, continuous monitoring required and records maintained in operating record	85	266.103(b)(7)					
submittal of revised certification of pre-compliance under 266.103(b)(2)&(3) procedures	85	266.103(b)(8)					
266.103(b)(6) public notice requirements not applicable to recertifications	85	266.103(b)(8)(i)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
operation of facility within limits established for 266.103(b)(3) parameters until 266.103(b) revised certification or 266.103(c) certification of compliance is submitted	85	266.103(b)(8)(ii)					
language of signed statement that must be included with the certification of precompliance	85	266.103(b)(9)					
conduct emissions testing to document compliance with 266.104(b)-(e), 266.105- 266.107 and 266.103(a)(5)(i) (D) emissions standards; submittal of certification of compliance on or before August 21, 1992	85,94	266.103(c)					
establish limits and all applicable emission standards on 266.103(c)(1)(i)-(xiii) parameters based on operations during compliance test or as otherwise specified and include with certification of compliance; device will be operated within these limits and applicable emission standards of 266.104(b)-(e), 266.105, 266.106, 266.107 and 266.103(a)(5)(i)(D) when hazardous waste is in the unit	85,94,96, 111,114	266.103(c)(1)					
feed rate of total hazardous waste and pumpable hazardous waste	85	266.103(c)(1)(i)					

dcbif99.rtf - Revised: 9/23/99

### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
17		85	266.103(c)(1)(ii)					
		85,111	266.103(c)(1)(ii) (A)					
			266.103(c)(1)(ii) (A)( <i>I</i> )					
		111	266.103(c)(1)(ii) (A)(2)					
		85	266.103(c)(1)(ii) (B)					
	feed rate of each metal in specified feedstreams	85,111,114	266.103(c)(1)(ii) (C)					
17	total feed rate of chlorine and chloride in total feed streams; the operating limits for facilities that comply with Tier I or Adjusted Tier I feed rate screening limits	85,111,114	266.103(c)(1)(iii)					
17	total feed rate of ash in total feedstreams, except ash feed rate for cement kilns and light- weight aggregate kilns is not limited	85,94	266.103(c)(1)(iv)					
17	carbon monoxide concentration and, where required, hydrocarbon concentration in stack gas; CO and HC limits	85	266.103(c)(1)(v)					

dcbif99.rtf - Revised: 9/23/99

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
17	maximum production rate when producing normal product, unless complying with Tier I or Adjusted Tier I feed rate screening limits for chlorine under 266.107(b)(1) or (e) and for all metals under 266.106(b) or (e), and uncontrolled particulate emissions do not exceed 266.105 standard	85,111,114	266.103(c)(1)(vi)					
17	maximum combustion chamber temperature with temperature measured where specified; exception	85,114	266.103(c)(1)(vii)					
17	maximum flue gas temperature entering a particulate matter control device; exception	85,114	266.103(c)(1)(viii)					
17		85,94	266.103(c)(1)(ix)					
			266.103(c)(1)(ix) (A)					
	limits for systems using wet		266.103(c)(1)(ix) (B)					
	scrubbers, including wet ionizing scrubbers; exception:	85	266.103(c)(1)(ix) (C)					
17	systems using venturi scrubbers, the minimum differential gas pressure across the venturi; exception	85	266.103(c)(1)(x)					
17		85,94,114	266.103(c)(1)(xi)					
		85	266.103(c)(1)(xi) (A)					
	limits for systems using dry scrubbers; exception:	85,114	266.103(c)(1)(xi) (B)					

dcbif99.rtf - Revised: 9/23/99

						STATE ANA		
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
17		85,94	266.103(c)(1)(xii)					
	limits for systems using wet ionizing scrubbers or		266.103(c)(1)(xii) (A)					
	electrostatic precipitators; exception	85	266.103(c)(1)(xii) (B)					
17	systems using fabric filters, the minimum pressure drop; exception	85	266.103(c)(1)(xiii)					
	at least 30 days prior to 266.103(c)(3) compliance testing, notify Director and submit required information:	85	266.103(c)(2)					
			266.103(c)(2)(i)					
			266.103(c)(2)(i) (A)					
			266.103(c)(2)(i)(B)					
			266.103(c)(2)(i)(C)					
	general facility information	85	266.103(c)(2)(i) (D)					
			266.103(c)(2)(ii)					
	specific information on each	85	266.103(c)(2)(ii) (A)					
	device to be tested		266.103(c)(2)(ii) (B)					
			266.103(c)(2)(ii) (C)					
			266.103(c)(2)(ii) (D)					
			266.103(c)(2)(ii) (D)(1)					
			266.103(c)(2)(ii) (D)(2)					

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
		266.103(c)(2)(ii) (D)(3)					
		266.103(c)(2)(ii) (E)					
		266.103(c)(2)(ii) (F)					

dcbif99.rtf - Revised: 9/23/99

Page 52 of 115 Printed: 11/19/99

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	information on testing planned, including complete copy of test		266.103(c)(2)(iii) 266.103(c)(2)(iii)					
	protocol and QA/QC plan, and summary description for each test that provides specified information	85	(A) 266.103(c)(2)(iii) (B)					
17	compliance testing under 266.103(b) and 266.103(c)(2) conditions; case by case approval to use compliance test data from one unit in lieu of testing a similar on-site unit; information required to support owner or operator request; approval based on 266.103(c) requirements	85,96	266.103(c)(3)(i)					
17	industrial furnaces that recycle collected particulate matter from air pollution control system must test to determine 266.106(c) or (d) metals standards compliance using one of the following procedures:	85	266.103(c)(3)(ii)					
17	266, Appendix IX testing requirements in "Alternative Method for Implementing Metals Controls"	85	266.103(c)(3)(ii) (A)					
17			266.103(c)(3)(ii) (B)					
	stack emissions testing for 6 hrs/day while hazardous waste	85	266.103(c)(3)(ii) (B)(1)					
	is burned during interim status; conditions for testing; analysis for metals content to assure		266.103(c)(3)(ii) (B)(2)					
	266.106(c) or (d) compliance; parameters for which operating limits must be		266.103(c)(3)(ii) (B)(3)					

operating limits must be established under 266.103(c) (3)

					STATE ANALOG IS:			
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
			266.103(c)(3)(ii) (B)(4)					
			266.103(c)(3)(ii) (B)(5)					
17	conduct compliance testing and establish limits on 266.103(c)(1) parameters after kiln system has been conditioned and has reached equilibrium with metals feed and metals emissions; conditions to be met during conditioning	85	266.103(c)(3)(ii) (C)					
17	if no simultaneous demonstration of 266.104- 266.107 compliance during a set of test runs, operating conditions of additional test runs as close as possible to original operating conditions	85	266.103(c)(3)(iii) (A)					
17	facility to operate under compliance test conditions and reach steady-state operations before obtaining test data to demonstrate 266.104-266.107 emissions standards compliance or establishing operating parameter limits; specific industrial furnaces need not reach steady-state conditions prior to beginning metals compliance testing	85	266.103(c)(3)(iii) (B)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	,
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
compliance test data obtained during emissions sampling are used to establish operating parameter limits in the certification of compliance when parameter must be established as per 266.103(c) (1)	85	266.103(c)(3)(iii) (C)					
within 90 days of completing compliance testing, certification to Director of compliance with 266.104(b),(c)&(e), 266.105-266.107 and 266.103(a)(5)(i) (D) emissions standards; certification must include:	85	266.103(c)(4)					
		266.103(c)(4)(i)					
		266.103(c)(4)(i) (A)					
	85	266.103(c)(4)(i)(B)					
	85,94	266.103(c)(4)(i)(C)					
		266.103(c)(4)(i) (D)					
		266.103(c)(4)(i)(E)					
		266.103(c)(4)(i)(F)					
		266.103(c)(4)(i)(G)					
general facility and testing		266.103(c)(4)(i) (H)					
information	85	266.103(c)(4)(i)(I)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
		266.103(c)(4)(ii)					
		266.103(c)(4)(ii) (A)					
		266.103(c)(4)(ii) (B)					
		266.103(c)(4)(ii) (B)(1)					
		266.103(c)(4)(ii) (B)(2)					
		266.103(c)(4)(ii) (B)(3)					
	85	266.103(c)(4)(ii) (B)(4)					
specific information on each test	85,94	266.103(c)(4)(ii) (B)(5)					
		266.103(c)(4)(ii) (B)(6)					
		266.103(c)(4)(ii) (B)(7)					
		266.103(c)(4)(ii) (B)(8)					
specific information on each test (con't)	85	266.103(c)(4)(ii) (B)(9)					
comparison of actual emissions per test with emissions limits prescribed by 266.104(b),(c)&(e) and 266.105-266.107 and established in 266.103(b) certification of precompliance	85	266.103(c)(4)(iii)					

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE	
determination of operating limits based on all valid runs for 266.103(c)(1) parameters using one of two procedures:	85	266.103(c)(4)(iv)						
instantaneous limits	85	266.103(c)(4)(iv) (A)						
		266.103(c)(4)(iv) (B)(1)						
		266.103(c)(4)(iv) (B)(1)(i)						
hourly rolling average basis as defined	85	266.103(c)(4)(iv) (B)(1)(ii)						
parameter operating limit based on compliance test data and specific average	85	266.103(c)(4)(iv) (B)(2)						
feed rate limits for carcinogenic metals and lead established on either an hourly rolling average basis or on (up to) 24-hour rolling average basis; requirements for 2- to 24-hour average period:	85	266.103(c)(4)(iv) (C)						
feed rate of each metal limited to ten times the allowable hourly rolling average basis feed rate	85	266.103(c)(4)(iv) (C)( <i>I</i> )						
		266.103(c)(4)(iv) (C)(2)						
	85	266.103(c)(4)(iv) (C)(2)(i)						
specifications the continuous monitor shall meet	85,94	266.103(c)(4)(iv) (C)(2)(ii)						

dcbif99.rtf - Revised: 9/23/99

Page 57 of 115

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
operating limit for feed rate of each metal established based on compliance test data as the specified average	85	266.103(c)(4)(iv) (C)(3)					
feed rate limits for metals, total chloride and chlorine, and ash established and monitored based on feedstream concentration and flow rate; flow rate continuously monitored as per 266.103(c) (4)(iv)(A)-(C)	85	266.103(c)(4)(iv) (D)					
language of statement to accompany the certification of compliance	85	266.103(c)(4)(v)					
8 if required to comply with 266.104(c) or 266.103(a)(5)(i) (D) HC controls, conditioned gas monitoring system may be used in conformance with 266, Appendix IX specifications, provided certification of compliance is submitted without 266.103(c)(7) time extension	85,111,144	266.103(c)(5)					
special operating requirements for industrial furnaces that recycle collected particulate matter from air pollution control system:	85	266.103(c)(6)					
266, Appendix IX operating requirements in "Alternative Method to Implement the Metals Controls" if complying with 266.103(c)(3)(ii)(A)	85	266.103(c)(6)(i)					
operating requirements of 266.103(c)(3)(ii)(B) if complying with that paragraph	85	266.103(c)(6)(ii)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
requirements if fail to submit complete certification of compliance for 266.104- 266.107 emissions standards by August 21, 1992:	85	266.103(c)(7)(i)					
stop burning hazardous waste and begin 266.103(l) closure	85,94	266.103(c)(7)(i) (A)					
limit hazardous waste burning only for purposes of compliance testing (and pretesting to prepare for compliance testing) to a total period of 720 hours beginning August 21, 1992; submit notification to Director by August 21, 1992, stating operation under restricted interim status and intention to resume hazardous waste burning; submit complete certification of compliance by August 23, 1993	85,94	266.103(c)(7)(i)(B)					
obtain case-by-case time extension under 266.103(c)(7) (ii)	85	266.103(c)(7)(i)(C)					
condition under which a case- by-case time extension may be requested for any 266.103(c) time limit	85	266.103(c)(7)(ii)					
in granting extension, Director may apply specified conditions	85	266.103(c)(7)(ii) (A)					
if time extension requested to enable facility to comply with alternative hydrocarbon provisions of 266.104(f) and to obtain RCRA permit because 266.104(c) HC limit cannot be met:	85,111	266.103(c)(7)(ii) (B)					

dcbif99.rtf - Revised: 9/23/99

						STATE ANA		
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	what Director shall consider:	85	266.103(c)(7)(ii) (B)(1)					
	determine if complete Part B permit application that includes 270.22(b) information has been submitted	85	266.103(c)(7)(ii) (B)( <i>I</i> )( <i>i</i> )					
	consider if good faith effort to certify compliance with all other emission controls has been made	85,94	266.103(c)(7)(ii) (B)( <i>I</i> )( <i>ii</i> )					
16	if extension granted, require facility to operate under 266.104(f)(1) baseline CO and HC flue gas concentration limits	85,94	266.103(c)(7)(ii) (B)(2)					
	submit at any time a revised certification of compliance under specific procedures:	85	266.103(c)(8)					
	prior to submittal, may not burn hazardous waste for more than 720 hours under operating conditions that exceed those in current certification of compliance; such burning conducted only to determine if 266.104-266.107 emissions standards can be met under revised conditions	85	266.103(c)(8)(i)					
	at least 30 days prior to first burning under revised conditions, notify Director and submit specific information:	85	266.103(c)(8)(ii)					
	EPA facility ID number, facility name, contact person, telephone number and address	85	266.103(c)(8)(ii) (A)					

dcbif99.rtf - Revised: 9/23/99

				STATE ANALOG IS:				
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE	
operating conditions owner/operator is seeking to revise and description of changes that prompted need to revise	85	266.103(c)(8)(ii) (B)						
determination that under revised operating conditions, 266.104-266.107 standards unlikely to be exceeded; 266.103(b)(2) information for documentation	85	266.103(c)(8)(ii) (C)						
complete emissions testing protocol for pretesting and new compliance test, including schedule for 266.104-266.107 emission standards compliance; 30-day prior written notice if revision in compliance test date	85	266.103(c)(8)(ii) (D)						
conduct compliance test under revised operating conditions and submitted protocol to determine 266.104-266.107 emissions standards compliance	85	266.103(c)(8)(iii)						
submit revised certification of compliance under 266.103(c) (4)	85	266.103(c)(8)(iv)						
recertification of compliance within three years; if recertification under new operating conditions, 266.103(c)(8) compliance	85	266.103(d)						

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
if noncompliance with interim status compliance schedule, burning is to terminate on date deadline is missed, closure to begin under 266.103(l), and no resumption of burning except under 270.66 operating permit; criteria for compliance with 266.103(l), 266.112(d)(2) and 266.113 provisions	85,96	266.103(e)					
no hazardous waste as feed during start-up and shut-down unless device is operating within certification conditions	85	266.103(f)					
during 266.103(c)(3) compliance test and upon certification of compliance, automatic waste feed cutoff required; additional requirements include:	85	266.103(g)					
maintenance of minimum combustion chamber temperature while hazardous waste or residues remain in chamber to minimize emissions of organic compounds	85,94	266.103(g)(1)					
if compliance with combustion chamber temperature limit is based on hourly rolling average, minimum temperature during compliance test is averaged over all runs of the lowest hourly rolling average for each run	85	266.103(g)(1)(i)					

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

					STATE AN	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
if compliance with combustion chamber temperature limit is based on instantaneous temperature measurement, minimum temperature during compliance test is time- weighted average during all test runs	85	266.103(g)(1)(ii)					
continued monitoring of operating parameters with limits during cutoff; no restart of hazardous waste feed until parameters comply with limits established in compliance certification	85	266.103(g)(2)					
		266.103(h)					
		266.103(h)(1)					
manyimamanta for controlling		266.103(h)(2)					
requirements for controlling fugitive emissions	85	266.103(h)(3)					
cease burning hazardous waste when changes in combustion properties, feed rates, feed stocks/fuels or design or operating conditions deviate from limits specified in compliance certification	85	266.103(i)					
owner or operator, while burning hazardous waste, must monitor and record:	85	266.103(j)(1)					
specified feed rates and composition of specified materials to ensure conformance with certification	85	266.103(j)(1)(i)					

Page 63 of 115

dcbif99.rtf - Revised: 9/23/99

					STATE ANALOG IS:					
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE			
CO, HC and oxygen on a continuous basis as specified; monitors installed, operated and maintained as per 266, Appendix IX methods	85	266.103(j)(1)(ii)								
sampling and analysis as requested by Director to verify compliance with 266.104- 266.107 standards	85	266.103(j)(1)(iii)								
daily visual inspection of boiler or industrial furnace and associated equipment when they contain hazardous waste	85	266.103(j)(2)								
test automatic feed cutoff system and associated alarms at least once every 7 days when hazardous waste is burned unless specified conditions are demonstrated; operational testing at least once every 30 days	85	266.103(j)(3)								
monitoring and inspection data recorded and placed in operating log	85	266.103(j)(4)								
all 266.103-required information and data kept in facility operating record until closure of the boiler or industrial furnace unit	85,96	266.103(k)								
remove all hazardous waste and hazardous waste residues at closure and comply with 265.111-265.115	85	266.103(l)								

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
STANDARDS TO CONTROL	ORGANIC E	EMISSIONS					
except as 266.104(a)(3) provides, DRE of 99.99% required for all organic hazardous constituents; demonstration during trial burn for each POHC in permit for each waste feed; DRE equation	85,94	266.104(a)(1)					
POHC compliance with DRE requirements to be demonstrated in trial burn in conformance with 270.66 procedures; designation of POHCs for each waste feed by Director based on degree of difficulty of destruction and on waste feed concentrations considering analyses submitted with Part B; 261, Appendix VIII compounds unless demonstration of other compound is suitable indicator of DRE requirements	85	266.104(a)(2)					
DRE of 99.9999% for F020-F023, F026 or F027 as determined from 266.104(a)(1) equation; notification of intent to burn such wastes	85,94	266.104(a)(3)					
owners and operators of boilers operating under 266.110 requirements are exempt from DRE trial burn	85	266.104(a)(4)					
owners and operators of boilers or industrial furnaces in compliance with 266.109(a) are exempt from DRE trial burn	85	266.104(a)(5)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
except as 266.104(c) provides, CO stack gas concentration cannot exceed 100 ppmv on an hourly rolling average basis, continuously corrected to 7% oxygen, dry gas basis	85	266.104(b)(1)					
continuous monitoring of CO and oxygen in conformance with 266, Appendix IX specifications	85,94	266.104(b)(2)					
demonstration of 100 ppmv CO compliance during trial burn or compliance test; highest hourly rolling average CO must not exceed 100 ppmv	85	266.104(b)(3)					
stack gas concentration of CO may exceed 100 ppmv if HC concentrations do not exceed 20 ppmv; exception under 266.104(f)	85	266.104(c)(1)					
HC limits established on hourly rolling average basis, reported as propane, continuously corrected to 7% oxygen, dry gas basis	85	266.104(c)(2)					
HC continuously monitored under 266, Appendix IX specifications; CO and oxygen continuously monitored under 266.104(b)(2)	85,94	266.104(c)(3)					
alternative CO standard based on trial burn data (new facility) and compliance test (interim status facility); definition and implementation	85	266.104(c)(4)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	<u> </u>
	CHECKLIST	FEDERAL RCRA	ANALOGOUS STATE	EQUIV-	LESS STRIN-	MORE STRIN-	BROADE R IN
FEDERAL REQUIREMENTS	REFERENCE	CITATION	CITATION	ALENT	GENT	GENT	SCOPE
industrial furnaces that feed							
hazardous waste for purpose							
other than solely as an							
ingredient at any location other							
than end where products are							
normally discharged and fuels							
are normally fired must							
comply with 266.104(c) or (f) hydrocarbon limits,							
irrespective of whether							
266.104(b) standard is met	85	266.104(d)					
		200.10 .(0)					
site-specific risk assessment							
for specific boilers and industrial furnaces to							
demonstrate that chlorinated							
dibenzo- <i>p</i> -dioxins and							
dibenzofurans emissions do not							
result in increased lifetime							
cancer risk exceeding 1 in							
100,000 MEI; assessment							
requirements:	85	266.104(e)					
determine emission rates of							
certain tetraocta congeners							
during trial burn or compliance							
test using 266, Appendix IX							
Method 23	85,94	266.104(e)(1)					
estimate 2,3,7,8-TCDD							
toxicity equivalence of							
specified congeners using 266,							
Appendix IX procedures;							
formula for estimation of							
equivalent emission rate	85,94	266.104(e)(2)					

dcbif99.rtf - Revised: 9/23/99

						STATE AN	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
us: to av co TC an us on to	induct dispersion modeling ing recommended methods predict maximum annual rerage off-site ground level incentrations of 2,3,7,8-CDD equivalents; maximum inual average concentration ed when a person resides a-site; wording should refer Appendix W, Part 51 rather an Appendix X, Part 266, ethods	85,125	266.104(e)(3)					
	ecified 2,3,7,8-TCDD ratio all not exceed 1.0	85,94,96	266.104(e)(4)					
C0 26	ment kilns may comply with O and HC limits under 66.104(b)-(d) by monitoring the by-pass duct provided:	85,94,111, 144	266.104(f)					
	e hazardous waste only into e kiln	85,144	266.104(f)(1)					
-	r-pass duct diverts minimum 10% of kiln off-gas into	85,94,144	266.104(f)(2)					
26 em sej op de CC est be tes	multaneous demonstration of 66.104 compliance by missions testing or during parate runs under identical perating conditions; data to emonstrate compliance with D and HC limits or to tablish alternative limits must be obtained during DRE sting, CDD/CDF testing and emprehensive organic missions testing	85,144	266.104(g)					

dcbif99.rtf - Revised: 9/23/99

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
19	compliance with permit operating requirements regarded as compliance with 266.104; if such compliance is insufficient, modification or revocation and reissuance of permit under 270.41	85,144	266.104(h)					
19	redesignated as 266.104(h)	144	266.104(i)					
	STANDARDS TO CONTROL	PARTICULA	ATE MATTER					
	particulate matter emissions limited to 180 milligrams per dry standard cubic meter after specified correction using Part 60, Appendix A, Methods 1-5 and 266, Appendix IX procedures	85	266.105(a)					
	owner or operator meeting 266.109(b) requirements for low risk waste exemption is exempt from particulate matter standard	85	266.105(b)					
	compliance with permit operating requirements regarded as compliance with 266.105; if such compliance is insufficient, modification or revocation and reissuance of permit under 270.41	85	266.105(c)					
	STANDARDS TO CONTROL	METALS EN	MISSIONS					
	compliance with 266.106(b), (c), (d), (e), or (f) for each 266.106(b) metal that is detectable in waste using specified procedures	85,94	266.106(a)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
Tier I feed rate screening limits for metals specified in 266, Appendix I as a function of terrain-adjusted effective stack height and terrain and land use in facility vicinity; criteria for ineligible facilities in 266.107(b)(7)	85	266.106(b)					
feed rates of antimony, barium, lead, mercury, thallium and silver in all feedstreams shall not exceed 266, Appendix I screening limits	85	266.106(b)(1)					
		266.106(b)(1)(i)					
what feed rate screening limits for antimony, barium, mercury, thallium, and silver are based		266.106(b)(1)(i) (A)					
on	85	266.106(b)(1)(i)(B)					
		266.106(b)(1)(ii)					
		266.106(b)(1)(ii) (A)					
		266.106(b)(1)(ii) (B)					
what feed rate screening limit for lead is based on	85	266.106(b)(1)(ii) (C)					
feed rates of arsenic, cadmium, beryllium and chromium in all feedstreams shall not exceed values derived from 266, Appendix I screening limits; feed rate limit equation	85,94	266.106(b)(2)(i)					

dcbif99.rtf - Revised: 9/23/99

					STATE ANALOG IS:					
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE			
		266.106(b)(2)(ii)								
what feed rate screening limits	85	266.106(b)(2)(ii) (A)								
for carcinogenic metals are based on	85,94	266.106(b)(2)(ii) (B)								
equation for terrain-adjusted effective stack height (TESH)	85	266.106(b)(3)(i)								
stack height may not exceed 40 CFR 51.100(ii) good engineering practice	85	266.106(b)(3)(ii)								
if TESH for a particular facility is not listed in table in appendices, nearest lower TESH to be used; if TESH # 4 meters, a value of 4 meters shall be used	85	266.106(b)(3)(iii)								
screening limits function of noncomplex or complex terrain; criteria; use U.S. Geological Survey 7.5-minute topographic maps	85	266.106(b)(4)								
screening limits function of urban or rural land use; determination using 266, Appendix IX or X	85,94	266.106(b)(5)								
facilities with multiple stacks must comply with screening limits for all units assuming all hazardous waste is fed into device with worst-case stack; worst-case stack equation, with lowest K value the worst-case stack	85,94	266.106(b)(6)								

dcbif99.rtf - Revised: 9/23/99

### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

					STATE A	NALOG IS:	1
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	85,111	266.106(b)(7)					
		266.106(b)(7)(i) 266.106(b)(7)(ii)					
criteria under which Tier III standards or Adjusted Tier I		266.106(b)(7)(iii)					
feed rate screening limits apply instead of Tier I and		266.106(b)(7)(iv)					
Tier II screening limits	85	266.106(b)(7)(v)					
monitor feed rate of metals in each feedstream to ensure screening limits are not exceeded	85	266.106(b)(8)					
Tier II emission rate screening limits function of stack height and terrain and land use in facility vicinity; ineligible facilities comply with 266.106(b)(7) criteria	85	266.106(c)					
emission rates of antimony, barium, lead, mercury, thallium and silver shall not exceed 266, Appendix I screening limits	85	266.106(c)(1)					
emission rates of arsenic, cadmium, beryllium and chromium shall not exceed values derived from 266, Appendix I screening limits; emission rate equation	85,94	266.106(c)(2)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
emission rate limits implemented by limiting individual metal feed rates to trial burn or compliance test levels; averaging periods; monitoring of metals feed rate in each feedstream to ensure compliance with 266.102 or 266.103 limits	85	266.106(c)(3)					
266.106(b) definitions and limitations for specified terms also apply to 266.106(c) Tier II emission rate screening limits	85	266.106(c)(4)					
facilities with multiple stacks must comply with emissions screening limits for any such stacks assuming all hazardous waste is fed into device with worst-case stack	85	266.106(c)(5)(i)					
worst-case stack determined by 266.106(b)(6) procedures	85	266.106(c)(5)(ii)					
for each metal, total emissions from those stacks shall not exceed worst-case stack screening limit	85	266.106(c)(5)(iii)					
facilities complying with either Tier III or Adjusted Tier I controls	111	266.106(d)					

Page 73 of 115

dcbif99.rtf - Revised: 9/23/99

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
21	conformance with Tier III metals control demonstrated by emissions testing; conformance with either Tier III or Adjusted Tier I metals controls demonstrated by air dispersion modeling; demonstration that acceptable ambient levels are not exceeded	85,111	266.106(d)(1)					
	266, Appendices IV and V list acceptable ambient levels; RACs listed for noncarcinogenic metals and 10 <sup>-5</sup> RSDs listed for carcinogenic metals; RSD defined	85	266.106(d)(2)					
	sum of the ratios of predicted ambient concentrations to risk- specific dose for all carcinogenic metals emitted shall not exceed 1.0; equation	85,94,111	266.106(d)(3)					
	for noncarcinogenic metals, predicted maximum annual average off-site ground level concentration shall not exceed the RAC	85	266.106(d)(4)					
	owners/operators with multiple stacks must conduct emissions testing and dispersion modeling to demonstrate that aggregate emissions do not exceed acceptable ambient levels; exception for facilities complying with Adjusted Tier I controls	85,111	266.106(d)(5)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
under Tier III, feed rates limited to trial burn or compliance test levels; averaging periods same as under 266.106(b)(1)(i)-(ii) and (b)(2)(ii); monitor metals feed rate in each feedstream to ensure 266.102 or 266.103 compliance	85	266.106(d)(6)					
Adjusted Tier I feed rate screening limits to account for site-specific dispersion modeling; how to estimate adjusted feed rate; feed rate screening limits for carcinogenic metals implemented under 266.106(b) (2)	85,94	266.106(e)					
alternative implementation approaches approved by Director on a case-by-case basis for Tier II or III metals emission limits	85	266.106(f)(1)					
		266.106(f)(2)					
	85	266.106(f)(2)(i)					
	85,94	266.106(f)(2)(ii)					
determination of 266.106(d) emissions limits for each	85	266.106(f)(2)(ii) (A)					
noncarcinogenic and carcinogenic metal	85,94	266.106(f)(2)(ii) (B)					
use 266, Appendix IX Multiple Metals Train to conduct emissions testing	85	266.106(g)(1)					

dcbif99.rtf - Revised: 9/23/99

#### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

					STATE AN	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
chromium emissions assumed to be hexavalent chromium unless owner/operator determines otherwise	85	266.106(g)(2)					
dispersion modeling conducted according to specified methods to predict maximum annual average off-site ground level concentration; on-site concentrations when person resides on-site	85,125	266.106(h)					
compliance with 266.102 permit operating requirements regarded as 266.106 compliance unless evidence indicates otherwise; modification or revocation and re-issuance of permit under 270.41	85	266.106(i)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
STANDARDS TO CONTROL	HYDROGEN	N CHLORIDE (HCI)	AND CHLO	RINE G	AS (CI <sub>2</sub> )	EMISS	IONS
compliance with HCl and Cl <sub>2</sub> controls under 266.107(b), (c) or (e)	85, 94,111	266.107(a)					
Tier I feed rate screening limits for total chlorine specified in 266, Appendix II as a function of stack height and terrain and land use in facility vicinity; feed rate of total chlorine and chloride in all feedstreams not to exceed specified levels	85	266.107(b)(1)					
Tier II emission rate screening limits for HCl and Cl <sub>2</sub> specified in 266, Appendix III as a function of terrainadjusted effective stack height and terrain and land use in facility vicinity; stack emission rates not to exceed specified levels	85,94	266.107(b)(2)					
266.106(b) definitions and limitations for specified terms also apply to 266.107(b) screening limits	85,94	266.107(b)(3)					
facilities with multiple stacks subject to HCl or Cl <sub>2</sub> emissions controls must comply with Tier I and II screening limits assuming all hazardous waste is fed into device with worst-case stack	85	266.107(b)(4)					
worst-case stack determined by 266.106(b)(6) procedures	85	266.107(b)(4)(i)					

Page 77 of 115

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
under Tier I, total feed rate of chlorine and chloride to all subject devices not to exceed worst-case stack screening limit	85	266.107(b)(4)(ii)					
under Tier II, total HCl and Cl <sub>2</sub> emissions from all subject stacks not to exceed worst-case stack screening limit	85	266.107(b)(4)(iii)					
conformance with Tier III controls demonstrated by HCl and Cl <sub>2</sub> emissions testing, air dispersion modeling, and demonstration that acceptable ambient levels are not exceeded	85	266.107(c)(1)					
266, Appendix IV lists RACs for HCl and Cl <sub>2</sub>	85	266.107(c)(2)					
facilities with multiple stacks subject to HCl or Cl <sub>2</sub> emissions controls must conduct emissions testing and dispersion modeling to demonstrate that aggregate emissions do not exceed acceptable ambient levels for HCl and Cl <sub>2</sub>	85	266.107(c)(3)					
2 HCl and Cl <sub>2</sub> controls implemented by limiting feed rate of total chlorine and	85	266.107(d)					
chloride in all feedstreams; feed rate under Tier I limited to Tier I screening limits; feed rate under Tiers II and III		266.107(d)(1)					
limited to trial burn or compliance test feed rates; feed rate limits based on:	85,94	266.107(d)(2)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
adjusted Tier I feed rate screening limits to account for site-specific dispersion modeling; how to determine these adjusted rates	85	266.107(e)					
emissions testing for HCl and Cl <sub>2</sub> conducted using 266, Appendix IX procedures	85	266.107(f)					
dispersion modeling conducted according to 266.106(h) provisions	85	266.107(g)					
compliance with 266.102 permit operating requirements regarded as 266.107 compliance unless evidence indicates otherwise; modification or revocation and re-issuance of permit under 270.41	85	266.107(h)					
SMALL QUANTITY ON-SIT	E BURNER E		<b>.</b>	ı	ı		<u> </u>
owners and operators that burn hazardous waste in on- site boiler or industrial furnace exempt from 266 Subpart H requirements provided:	85,94	266.108(a)					
quantity of hazardous waste burned for a calendar month does not exceed limits shown in table titled "Exempt Quantities for Small Quantity Burner Exemption" based on 266.106(b)(3) terrain-adjusted effective stack height; table	85,94	266.108(a)(1)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
maximum hazardous waste firing rate does not exceed 1% of total fuel requirements on a total heat input or mass input basis, whichever results in the lower mass feed rate of hazardous waste	85,96	266.108(a)(2)					
minimum heating value of 5,000 Btu/lb	85	266.108(a)(3)					
does not contain F020-F023, F026 or F027	85	266.108(a)(4)					
if mixed with non-hazardous waste, compliance with 266.108(a) quantity before mixing	85	266.108(b)					
equation for implementing 266.108(a)(1) quantity limits if burning in more than one exempt on-site boiler or industrial furnace	85,94,111	266.108(c)					
		266.108(d)					
one-time signed, written		266.108(d)(1)					
notification requirements for small quantity burner		266.108(d)(2)					
exemption exemption	85	266.108(d)(3)					
maintain for at least 3 years sufficient records documenting quantity firing rate and heating value limits compliance, including quantity burned per calendar month and heating value	85	266.108(e)					

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

Page 80 of 115

	CHECKLIST				STATE A	NALOG IS:	1
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
LOW RISK WASTE EXEMP	ΓΙΟΝ		_			1	
waiver of 266.104(a) DRE standard if device is operated in conformance with 266.109(a)(1) and burning will not result in unacceptable adverse health effects as per 266.109(a)(2) procedures	85	266.109(a)					
	85	266.109(a)(1)					
	85,94,96	266.109(a)(1)(i)					
		266.109(a)(1)(ii)					
operating requirements for		266.109(a)(1)(iii)					
device	85	266.109(a)(1)(iv)					
		266.109(a)(2)					
		266.109(a)(2)(i)					
		266.109(a)(2)(ii)					
		266.109(a)(2)(iii)					
		266.109(a)(2)(iii) (A)					
	85	266.109(a)(2)(iii) (B)					
		266.109(a)(2)(iv)					
	85,94	266.109(a)(2)(iv) (A)					
procedures to demonstrate that hazardous waste burning		266.109(a)(2)(iv) (B)					
will not pose unacceptable adverse public health effects	85	266.109(a)(2)(iv) (C)					
		266.109(b)					
conditions under which the 266.105 particulate matter	85	266.109(b)(1)					

266.105 particulate matter standard is waived

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

	I	1	1	1			
					STATE A	NALOG IS:	ı
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	85,94	266.109(b)(2)					
WAIVER OF DRE TRIAL BU	RN FOR BO	ILERS	•	-		-	-
boilers operating under 266.110 requirements and that do not burn F020-F023, F026 or F027 considered in compliance with 266.104(a) DRE standard, and trial burn to demonstrate DRE is waived; when burning hazardous waste:	85	266.110					
"primary fuel" defined; minimum of 50% primary fuel firing rate, determined on total heat or mass input basis, whichever results in the greater mass feed rate	85,96	266.110(a)					
boiler load defined and not less than 40%	85	266.110(b)					
minimum as-fired heating value of 8,000 Btu/lb	85	266.110(c)					
conformance with 266.104(b) (1) carbon monoxide standard; boilers subject to 266.110 DRE waiver not eligible for 266.104(c) alternative carbon monoxide standard	85	266.110(d)					
boiler must be water-tube type that does not feed fuel using a stoker or stoker type mechanism	85	266.110(e)					

dcbif99.rtf - Revised: 9/23/99

#### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
conditions under which		266.110(f)					
hazardous waste shall be fired		266.110(f)(1)					
directly into primary fuel flame zone of combustion chamber with an air or steam,	85	266.110(f)(2)					
	85,94	266.110(f)(3)					
mechanical or rotary cup atomization system	85	266.110(f)(4)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
STANDARDS FOR DIRECT	TRANSFER	_	1				ı
266.111 regulations apply to boilers and industrial furnaces subject to 266.102 or 266.103 if direct transfer of hazardous waste from transport vehicle to boiler or industrial furnace without use of storage unit	85	266.111(a)					
for 266.111, terms have meanings given in 266.111(b)	85	266.111(b)(1)intro					
"direct transfer equipment"	85	266.111(b)(1)					
"container"	85	266.111(b)(1)					
"tank systems" means direct transfer equipment when Subparts I and J of Parts 264 and 265 are referenced	85	266.111(b)(2)					
no direct transfer of pumpable hazardous waste from open- top container to boiler or industrial furnace	85	266.111(c)(1)					
direct transfer equipment requirements	85	266.111(c)(2)					
		266.111(c)(3)					
		266.111(c)(3)(i)					
		266.111(c)(3)(ii)					
		266.111(c)(3)(iii)					
direct transfer of hazardous waste to boiler or industrial		266.111(c)(3)(iv)					
furnace conducted so that it does not result in any		266.111(c)(3)(v)					
266.111(c)(3)(i)-(vi) situation	85	266.111(c)(3)(vi)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
conditions under which hazardous waste shall not be placed in direct transfer equipment	85	266.111(c)(4)					
appropriate controls and		266.111(c)(5)					
practices to prevent spills and overflows from direct transfer equipment or its secondary		266.111(c)(5)(i)					
containment system	85	266.111(c)(5)(ii)					
applying 266.111(b)(1) definition of container, owners and operators must comply with:	85	266.111(d)					
264.175 containment requirements	85	266.111(d)(1)					
use and management requirements of Subpart I, Part 265 requirements, except 265.170 and 265.174; compliance with specified maintenance and protective distances in lieu of 265.176 requirements; written certification by local fire marshall to be kept on file	85,96	266.111(d)(2)					
264.178 closure requirements	85	266.111(d)(3)					
direct transfer equipment must meet following requirements:	85	266.111(e)					
		266.111(e)(1)					
secondary containment requirements for new and		266.111(e)(1)(i)					
existing equipment	85	266.111(e)(1)(ii)					

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

Page 85 of 115

					STATE ANALOG IS:			
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE	
for existing direct transfer equipment without secondary containment, determination whether leaking or unfit for use; written assessment reviewed and certified by qualified, registered professional engineer in accordance with 270.11(d) by August 21, 1992	85	266.111(e)(2)(i)						
		266.111(e)(2)(ii)						
		266.111(e)(2)(ii) (A)						
		266.111(e)(2)(ii) (B)						
		266.111(e)(2)(ii) (C)						
		266.111(e)(2)(ii) (D)						
minimum considerations for assessment	85	266.111(e)(2)(ii) (E)						
if, due to 266.111(e)(2)(i)&(ii) assessment, direct transfer equipment found to be leaking or unfit for use, compliance with 265.196(a) and (b)	85	266.111(e)(2)(iii)						
		266.111(e)(3)(i)						
inspection requirements at least once each operating hour		266.111(e)(3)(i) (A)						
when transferring hazardous waste from container to boiler		266.111(e)(3)(i)(B)						
or industrial furnace	85	266.111(e)(3)(i)(C)						
inspect cathodic protection systems to ensure 265.195(b) compliance	85	266.111(e)(3)(ii)						

dcbif99.rtf - Revised: 9/23/99

						STATE A	NALOG IS:	
_	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
n	ecords of inspections maintained in operating record for at least 3 years	85	266.111(e)(3)(iii)					
a	265.192 compliance for design and installation of new ancillary equipment	85	266.111(e)(4)					
	265.196 compliance for esponse to leaks or spills	85	266.111(e)(5)					
	265.197 closure compliance, except 265.197(c)(2)-(4)	85	266.111(e)(6)					
23 <u>F</u>	REGULATION OF RESIDUE	S		_	1			1
v 2 d	esidue derived from burning or processing of hazardous waste is not excluded under 261.4(b)(4), (7) or (8) unless device and owner or operator meet the following equirements:	85,94	266.112					
24		85	266.112(a)					
		85,96	266.112(a)(1)					
			266.112(a)(2)					
c	criteria the device must meet:	85	266.112(a)(3)					
d re	demonstration by owner or operator that hazardous waste loes not significantly affect esidue by demonstrating conformance with either of wo criteria:	85	266.112(b)					
re fe	comparison of waste-derived esidue with normal residue for 261, Appendix VIII constituents; procedures to be used	85	266.112(b)(1)					

dcbif99.rtf - Revised: 9/23/99

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
determination of concentrations of toxic constituents of concern in normal residue based on analyses of a minimum of 10 samples representing a minimum of 10 days of operation; determine compositing period not to exceed 24 hours; upper tolerance limit (at 95% confidence with a 95% proportion of the sample distribution) for the statistically-derived concentration; when to revise; how to determine the upper tolerance limit	85,96	266.112(b)(1)(i)					
sampling and analysis of waste-derived residue to determine whether residue generated during each 24-hour period has concentrations of toxic constituents higher than 266.112(b)(1)(i) normal residue concentrations; if so, residue not excluded from definition of hazardous waste; toxic constituent concentrations based on analysis of samples obtained over 24-hour period; for multiple samples, concentration of toxic constituent is arithmetic mean; no results may be disregarded	85,96	266.112(b)(1)(ii)					

dcbif99.rtf - Revised: 9/23/99

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
25	concentration of each nonmetal toxic constituent of concern in waste-derived residue must not exceed health-based limits specified in 266, Appendix VII or level detection using SW-846 analytical procedures; if no limit in Appendix VII, limit is 0.002 mg/kg or level of detection, whichever is higher; levels specified in appendix VII and default level of 0.002 micrograms/kg or level of detection as identified in Note 1 are administratively stayed; owner or operator must comply with alternative levels defined as land disposal restriction limits specified in § 268.43 for F039 nonwastewaters; compliance based on good-faith effort to detect constituents; demonstration of good-faith efforts; stay in effect until further administrative action is taken	85,111,†127	266.112(b)(2)(i)					
	for metal constituents, in extract concentration obtained using 261.24 TCLP not to exceed 266, Appendix VII							
	limits	85	266.112(b)(2)(ii)					

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

Page 89 of 115

					CTATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
sampling and analysis of waste-derived residue to determine whether residue generated during each 24-hour period has concentrations of toxic constituents higher than health-based levels; determination of toxic concentrations based on analysis of one or more samples obtained over 24-hour period; for multiple samples, concentration of toxic constituent is arithmetic mean of concentrations in samples; no results may be disregarded	96	266.112(b)(2)(iii)					
	85,96	266.112(c)					
records to document 266.112 compliance to be retained until closure of boiler or industrial furnace unit; information to be recorded	85	266.112(c)(1) 266.112(c)(2) 266.112(c)(2)(i) 266.112(c)(2)(ii)					
_	AP	PENDIX I TO PAR	Г 266				
TIER I AND TIER II FEED RA	ATE AND EM	IISSIONS SCREENI	NG LIMITS	FOR ME	ETALS		
Tier I and Tier II Feed Rate and Emissions Screening Limits for Noncarcinogenic Metals for Facilities in Noncomplex Terrain (see 56 FR 7228 and 56 FR 32690 or the July 1, 1992 CFR)	85,94	Appendix I/Table I-A					
Tier I and Tier II Feed Rate and Emissions Screening Limits for Noncarcinogenic Metals for Facilities in Noncomplex Terrain (see 56 FR 7229)	85	Appendix I/Table I-B					

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

Page 90 of 115

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
Tier I and Tier II Feed Rate and Emissions Screening Limits for Noncarcinogenic Metals for Facilities in Complex Terrain (see 56 <u>FR</u> 7229)	85	Appendix I/Table I-C					
Tier I and Tier II Feed Rate and Emissions Screening Limits for Carcinogenic Metals for Facilities in Noncomplex Terrain (see 56 FR 7230 and 56 FR 32690 or the July 1, 1992 CFR)	85,94	Appendix I/Table I-D					
Tier I and Tier II Feed Rate and Emissions Screening Limits for Carcinogenic Metals for Facilities in Complex Terrain (see 56 FR 7230 and 56 FR 32690, or the July 1, 1992 CFR)	85,94	Appendix I/Table I-E					
	AI	PPENDIX II TO PAR	RT 266				
TIER I FEED RATE LIMITS	FOR TOTAL	CHLORINE					
26 Tier I feed rate screening limits for chlorine for facilities in noncomplex and complex terrain (see 56 FR 32690-32691 or the July 1, 1992 CFR)	85,94	Appendix II					
	AP	PENDIX III TO PAI	RT 266				
TIER II EMISSION RATE S	CREENING L	IMITS FOR FREE C	HLORINE A	ND HYD	ROGEN	CHLO	RIDE
26 Tier II emissions screening limits for Cl <sub>2</sub> and HCl in noncomplex and complex terrain (see 56 <u>FR</u> 32691 or the July 1, 1992 CFR)	85,94	Appendix III					

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

Page 91 of 115

1							
					STATE A	NALOG IS:	•
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	API	PENDIX IV TO PAI	RT 266				
REFERENCE AIR CONCENT	ΓRATIONS						
Constituents, CAS Nos. and RAC (see 56 FR 7232 and 56 FR 32691 or the July 1, 1992 CFR)	85,94	Appendix IV					
	AP	PENDIX V TO PAR	T 266	-	-	-	-
RISK SPECIFIC DOSES							
Constituents, CAS Nos., Unit risk and RsD (see 56 FR 7232-7233 or the July 1, 1992 CFR)	85	Appendix V					
	API	PENDIX VI TO PAR	RT 266				
STACK PLUME RISE							
flow rates and exhaust temperatures (see 56 <u>FR</u> 7233-7234 or the July 1, 1992 CFR)	85	Appendix VI					
	APP	ENDIX VII TO PAI	RT 266				
HEALTH-BASED LIMITS FO	OR EXCLUSION	ON OF WASTE-DE	RIVED RESI	DUES			
MetalsTCLP Extract Concentration Limits (56 <u>FR</u> 7234 and 56 <u>FR</u> 32691 or the July 1, 1992 CFR)	85,94	Appendix VII					

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

Page 92 of 115

#### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
NonmetalsResidue Concentration Limits (see 56 FR 7234 and 56 FR 32691 or the July 1, 1992 CFR); include note regarding administrative stay of specified and default levels for constituents specified in § 266.112(b)(1) provided owner or operator complies with alternative levels defined in							
266.112(b)(2)(i)	85,94, †127	Appendix VII					

dcbif99.rtf - Revised: 9/23/99

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
		APP	ENDIX VIII TO PA	RT 266				
	POTENTIAL PICs FOR DETE	ERMINATION	N OF EXCLUSION (	OF WASTE-I	DERIVE	D RESII	DUES	
	PICs Found in Stack Effluents (see 56 FR 7235 and 56 FR 32691 or the July 1, 1992 CFR)	85,94	Appendix VIII					
		API	- PENDIX IX TO PAR	T 266	•	•	-	•
	METHODS MANUAL FOR C	COMPLIANCI	E WITH BIF REGUI	LATIONS				
27	Burning Hazardous Waste in Boilers and Industrial Furnaces (see 56 FR 32692- 32795 or the July 1, 1992 CFR)	85,94	Appendix IX					
27	Classification of Land Use Types (see 56 <u>FR</u> 32770 and 57 <u>FR</u> 38566)	85,94,111	Appendix IX/ Section 5.0/ Table 5.0-3					
	ISCST Predicted Maximum Concentrations (see 56 <u>FR</u> 32771; 57 <u>FR</u> 38566; and 57 <u>FR</u> 44999)	85,94, 111,114	Appendix IX/ Section 5.0/ Table 5.0-4					
27,28	ISCST Predicted Maximum Concentrations (see 56 <u>FR</u> 32772-32773; 57 <u>FR</u> 38566; and 57 <u>FR</u> 44999)	85,94, 111,114	Appendix IX/ Section 5.0/ Table 5.0-5					
27	Simplified Land Use Classification Procedure for Compliance with Tier I and Tier II Limits (see 56 FR 32782-32783 or the July 1, 1991 CFR; and 57 FR 38566)	85,94,111	Appendix IX/ Section 6.0					
27, 29	Statistical Methodology for Bevill Residue Determinations (see 56 FR 42516 & 42517)	85,94,96	Appendix IX/ Section 7.0					

dcbif99.rtf - Revised: 9/23/99

Page 94 of 115 Printed: 11/19/99

						STATE A	NALOG IS:	
	FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
27	Special procedures for chlorine, HCl and CL <sub>2</sub> (see 56 FR 32786-32787 and 56 FR 42512, Corrections 6 and 7 under Part 270; note these corrections should have been placed under Part 266)	85,94,96	Appendix IX/ Section 9.2					
30	Statistics (see 56 <u>FR</u> 32796 or the July 1, 1992 CFR)	85,94	Appendix A to Appendix IX					
31		APPENDIX	X X TO PART 266	(REMOVED)	)			
	GUIDELINE ON AIR QUALI	TY MODELS	(REVISED)					
	removed	85,94,125	Appendix X					
		API	PENDIX XI TO PAR	RT 266	-	-		
	LEAD-BEARING MATERIAL	S THAT MA	Y BE PROCESSED	IN EXEMPT	LEAD	SMELTE	ERS	
	add new appendix addressing lead-bearing materials that may be processed in exempt lead smelters (see 56 <u>FR</u> 42517)	96	Appendix XI					
	,	APF	PENDIX XII TO PAI	RT 266	<b>a</b>	<b>-</b>		
	NICKEL- OR CHROMIUM-B CHROMIUM RECOVERY FU		TERIALS THAT M	AY BE PROC	CESSED	IN EXE	MPT NI	CKEL-
	add new appendix addressing nickel or chromium-bearing materials that may be processed in exempt nickel-chromium recovery furnaces (see 56 FR 42517)	96	Appendix XII					
32		APP	ENDIX XIII TO PA	RT 266				
	MERCURY BEARING WAST UNITS	ES THAT M	AY BE PROCESSEI	O IN EXEMP	T MERO	CURY RI	ECOVEI	RY

dcbif99.rtf - Revised: 9/23/99

#### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

					STATE AN	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
add new appendix addressing certain mercury-bearing							
wastes	137	Appendix XIII					

dcbif99.rtf - Revised: 9/23/99

					STATE AN	NALOG IS:	
			ANALOGOUS		LESS	MORE	BROADE
	CHECKLIST	FEDERAL RCRA	STATE	EQUIV-	STRIN-	STRIN-	R IN
FEDERAL REQUIREMENTS	REFERENCE	CITATION	CITATION	ALENT	GENT	GENT	SCOPE

#### PART 270 - EPA ADMINISTERED PERMIT PROGRAMS: THE HAZARDOUS WASTE PERMIT PROGRAM

#### SUBPART B - PERMIT APPLICATION

### 33 SPECIFIC PART B INFORMATION REQUIREMENTS FOR BOILERS AND INDUSTRIAL FURNACES BURNING HAZARDOUS WASTE

owners and operators subject to 266.104-266.107 must conduct a trial burn and must submit a trial burn plan or results in accordance with 270.66	85	270.22(a)(1)			
waiver of trial burn to demonstrate conformance with a particular emission standard under 266.104- 266.107 and 270.22(a)(2)-(a) (5)	85	270.22(a)(1)(i)			
data in lieu of a trial burn as 270.22(a)(6) specifies	85	270.22(a)(1)(ii)			
boiler owners and operators seeking to be permitted under 266.104(a)(4) and 266.110, must submit documentation showing boiler compliance with special operating requirements at 266.110; trial burn waived	85	270.22(a)(2)(i)			
		270.22(a)(2)(ii)			
information that must be	85	270.22(a)(2)(ii)(A)			
submitted for boilers and industrial furnaces seeking to		270.22(a)(2)(ii)(B)			
be permitted under the low	85,94	270.22(a)(2)(ii)(C)			
risk waste provisions of 266.104(a)(5) and 266.109(a)		270.22(a)(2)(ii)(D)			
without a trial burn	85	270.22(a)(2)(ii)(E)			

Page 97 of 115

dcbif99.rtf - Revised: 9/23/99

#### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADI R IN SCOPE
		270.22(a)(3)					
		270.22(a)(3)(i)					
		270.22(a)(3)(ii)					
		270.22(a)(3)(iii)					
information that must be		270.22(a)(3)(iv)					
submitted when seeking to be permitted under Tier I metals		270.22(a)(3)(v)					
feed rate screening limits at 266.106(b)&(e) without a trial		270.22(a)(3)(vi)					
burn	85	270.22(a)(3)(vii)					
when seeking to be permitted under the low risk waste provisions of 266.109(b) which waives the particulate standard, submit documentation supporting 270.22(a)(2)(ii) and (a)(3)							
conformance	85	270.22(a)(4)					
		270.22(a)(5)					
		270.22(a)(5)(i)					
		270.22(a)(5)(ii)					
information to be submitted		270.22(a)(5)(iii)					
when seeking to be permitted under Tier I feed rate screening limits for total		270.22(a)(5)(iv)					
		270.22(a)(5)(v)					
chloride and chlorine under 266.107(b)(1) and (e)	85	270.22(a)(5)(vi)					
provisions without a trial burn	85,94	270.22(a)(5)(vii)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
owner or operator may seek exemption from trial burn requirements demonstrating 266.104-266.107 conformance, by providing information from previous compliance testing of the device or compliance testing or trial burns of similar boilers or industrial furnaces; burning similar wastes under similar conditions 270.66 design and operation information required; conditions under which Director shall approve a permit application in lieu of a trial burn; additional							
information to be submitted	85,94	270.22(a)(6)					
		270.22(a)(6)(i)					
		270.22(a)(6)(i)(A)					
for a waiver from any trial		270.22(a)(6)(i)(B)					
burn:	85	270.22(a)(6)(i)(C)					
for a waiver of DRE trial burn, basis for selection of the POHCs used in other burns which demonstrate 266.104(a) compliance; analysis should specify 261, Appendix VIII constituents in hazardous waste for which a permit is sought and any differences from POHCs for which data are provided	85	270.22(a)(6)(ii)					

dcbif99.rtf - Revised: 9/23/99

Page 99 of 115 Printed: 11/19/99

				STATE ANALOG IS:					
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE		
	85	270.22(b)							
	85,94	270.22(b)(1)							
		270.22(b)(2)							
		270.22(b)(3)							
		270.22(b)(4)							
minimum information to be		270.22(b)(4)(i)							
submitted for industrial furnaces with organic matter		270.22(b)(4)(ii)							
in raw materials requesting an		270.22(b)(5)							
alternative HC limit under 266.104(f)	85	270.22(b)(6)							
when seeking to be permitted under 266.106(f) alternative metals implementation approach, submit documentation that ensures 266.106(c) or (d) compliance and how approach can be implemented and monitored; provide other information as Director finds necessary	85	270.22(c)							
describe automatic waste feed cutoff system, including any pre-alarm systems	85	270.22(d)							
use of direct transfer operations requires submittal of information supporting 266.111 conformance	85	270.22(e)							
demonstration of 266.112 conformance if claim is made that residues are excluded from regulation	85	270.22(f)							

dcbif99.rtf - Revised: 9/23/99

				1			
					STATE A	NALOG IS:	
FEDERAL REQUIREM	CHECK IENTS REFERE		ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	SUI	BPART D - CHANGE	S TO PERMITS				
34 PERMIT MODIFIC	ATION AT THE R	REQUEST OF THE PE	ERMITTEE	_			
replace "270.21" with and "and 270.63" with and 270.66"		270.42(c)(1)(iv)					
paragraph heading is to "Newly regulated and units"	_	270.42(g)					
add wording at end o paragraph regarding continued manageme hazardous waste in u newly regulated as ha waste management u change "wates" to "v	the nt of nits azardous nits;	270.42(g)(1)					
insert "The unit" before in existence"; add "or regulated waste man unit" after "character waste"; add "or regulated unit" at end of paragraph change "effetive" to "effective"	newly agement ized ating the	270.42(g)(1)(i)					
insert "The permittee "submits"; insert "or u "waste"		270.42(g)(1)(ii)					
insert "The permittee "is"; insert "applicable "standards"; change ' to "Parts 265 and 266 chapter"	e" before 'Part 265"	270.42(g)(1)(iii)					

dcbif99.rtf - Revised: 9/23/99

#### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
delete "In the case of Classes 2 and 3 modifications,"; insert "The permittee" before "also"; replace "permit modification" with "Class 2 or 3 modification"; change "180 days after" to "180 days of"; add "or subjecting the unit to RCRA Subtitle C management standards" to end of paragraph	85,94	270.42(g)(1)(iv)					
insert "the permittee" before "certifies"; insert "each" before "such unit"; change "Part 265" to "requirements of Part 265 of this chapter for"; add ", or regulating the unit as a hazardous waste management unit" after "hazardous"; change "clarify" to "certify"; insert "all" before "these requirements"; change "shall lose" to "will lose"	85	270.42(g)(1)(v)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
	CHECKI IST	EEDED AL DOD A	ANALOGOUS	FOLIN	LESS	MORE	BROADE
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	STATE CITATION	EQUIV- ALENT	STRIN- GENT	STRIN- GENT	R IN SCOPE
change heading of "L." to							
"Incinerators, Boilers, and							
Industrial Furnaces"; in "L.1."							
& "L.2." replace "a waste							
feed rate limit, or an organic							
feed rate limit" with "a feed-							
stream feed rate limit, a							
chlorine/chloride feed rate							
limit, a metal feed rate limit, or							
an ash feed rate limit"; in							
"L.3." replace "HCl" with							
"HCl/Cl <sub>2</sub> metals,"; in "L.3." &							
"L.4." insert ", boiler, or							
industrial furnace" after							
"incinerator"; in "L.5." replace							
"." after "requirements" with							
":"; in "L.5.a." insert "or							
maximum" before "combustion							
gas temperature" & add "flue							
gas carbon monoxide and							
hydro-carbon concentration,							
maximum temperature at the							
inlet to the particulate matter							
emission control system, or							
operating parameters for the							
air pollution control system"							
after "chamber"; change "L.6."							
heading to "Burning different							
wastes:"; in "L.6.a." change							
"incineration" to "burning"; in							
"L.6.a. & b." change all "to							
incinerate" to "to burn"; in							
"7.b." change "waste							
incineration" to "waste							
burning"; in "L.8." insert "non-							
hazardous waste" before							
"fuel"	85,94	270.42/Appendix I					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
	SUBPART F	- SPECIAL FORMS	S OF PERMIT	ΓS			
PERMITS FOR BOILERS AN	D INDUSTRI	AL FURNACES BU	JRNING HAZ	ZARDOU	JS WAS	TE	
new boilers and industrial furnaces subject to 270.66(b)- (f); those under interim status standards of 266.103 subject to 270.66(g)	85	270.66(a)					
permit for new boiler or industrial furnace shall specify appropriate conditions for the following operating periods:	85	270.66(b)					
pretrial burn period described; Director must establish in Pretrial Burn Period of permit conditions, allowable hazardous waste feed rates and operating conditions; extension of period for up to 720 additional hours; permit may be modified to reflect extension as per 270.42	85	270.66(b)(1)					
submittal of statement with Part B that suggests operating conditions for 266.104-266.107 compliance during period, including restrictions on 266.102(e) operating requirements	85	270.66(b)(1)(i)					
review of Part B materials and specification by Director of requirements sufficient to meet 266.104-266.107 performance standards based on engineering judgment	85 111,114	270.66(b)(1)(ii)					

dcbif99.rtf - Revised: 9/23/99

-					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
for duration of trial burn, Director establishes conditions in permit to determine feasibility of compliance with 266.104-266.107 standards and to determine adequate 266.102(e) operating conditions; applicants must propose a trial burn plan as per 270.66(c) and submit with Part B	85	270.66(b)(2)					
for defined minimum period immediately following trial burn, during which submission and review of trial burn results and modification of permit by Director occurs, Director establishes operating requirements most likely to ensure compliance with 266.104-266.107 standards	85	270.66(b)(3)(i)					
submittal of statement with Part B that identifies operating conditions for 266.104-266.107 compliance during period, including restrictions on 266.102(e) operating requirements	85	270.66(b)(3)(ii)					
review and specification by Director of requirements sufficient to meet 266.104- 266.107 performance standards based on engineering judgment	85	270.66(b)(3)(iii)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADI R IN SCOPE
for final period of operation Director develops operation requirements in conformar with 266.102(e) and 266.10 266.107 standards; Director shall make necessary modifications to permit as 270.42 based on trial burn results to ensure compliance	g nce 04- or per	270.66(b)(4)					
information the trial burn p must include; Director may require supplemental information		270.66(c)					
		270.66(c)(1)					
		270.66(c)(1)(i)					
analysis of each feedstream as fired	m, 85	270.66(c)(1)(ii)					
	85	270.66(c)(2)					
		270.66(c)(2)(i)					
1 . 6 . 1 . 1	85,94	270.66(c)(2)(ii)					
analysis of each hazardous waste, as fired	85	270.66(c)(2)(iii)					
		270.66(c)(3)					
		270.66(c)(3)(i)					
		270.66(c)(3)(ii)					
		270.66(c)(3)(iii)					
		270.66(c)(3)(iv)					
	85	270.66(c)(3)(v)					
		270.66(c)(3)(vi)					
detailed engineering description of boiler or	85,94	270.66(c)(3)(vii)					
industrial furnace	85	270.66(c)(3)(viii)					

dcbif99.rtf - Revised: 9/23/99

					STATE A	NALOG IS:	
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
detailed description of sampling and monitoring procedures	85	270.66(c)(4)					
detailed test schedule for each hazardous waste for which the trial burn is planned	85	270.66(c)(5)					
detailed test protocol	85	270.66(c)(6)					
description of, and planned operating conditions for, any emission control equipment to be used	85	270.66(c)(7)					
procedures for rapid stopping of hazardous waste feed and emissions control if an equipment malfunction	85	270.66(c)(8)					
other information Director finds necessary	85	270.66(c)(9)					
trial burn conducted to demonstrate conformance with 266.104-266.107 standards under an approved trial burn plan	85	270.66(d)(1)					
		270.66(d)(2)					
		270.66(d)(2)(i)					
		270.66(d)(2)(ii)					
findings under which the Director shall approve a trial		270.66(d)(2)(iii)					
burn plan	85	270.66(d)(2)(iv)					
submit to Director within 90 days of trial burn completion a certification that trial burn was carried out in accordance with approved plan and results of all 270.66(c) required determinations	85	270.66(d)(3)					

dcbif99.rtf - Revised: 9/23/99

				STATE ANALOG IS:			
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
submit all data collected during any trial burn	85	270.66(d)(4)					
270.66(d) submissions must be certified by signature of person authorized to sign permit application or 270.11 report	85	270.66(d)(5)					
for DRE trial burn under 266.104(a), Director will specify trial POHCs; basis for specification	85	270.66(e)					
determinations to be made based on each trial burn:	85	270.66(f)					
quantitative analysis of specified materials in the feedstreams	85	270.66(f)(1)					
		270.66(f)(2)					
		270.66(f)(2)(i)					
determinations needed when a DRE trial burn is required		270.66(f)(2)(ii)					
under 266.104(a)	85	270.66(f)(2)(iii)					
quantitative analysis of stack gas and a computation showing conformance with the emission standard when a trial burn is required for chlorinated dioxins and furans under 266.104(e)	85,94	270.66(f)(3)					

dcbif99.rtf - Revised: 9/23/99

#### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

				STATE ANALOG IS:			
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
quantitative analysis of stack gas and computations showing conformance with applicable emission standards when a trial burn is required for particulate matter, metals, or HCl/Cl <sub>2</sub> under 266.105, 266.106(c) or (d), or 266.107(b)(2) or (c)	85	270.66(f)(4)					
quantitative analysis of scrubber water, ash residues, other residues and products to estimate fate of trial POHCs, metals, and chlorine/chloride when a trial burn is required for DRE, metals or HCl/Cl <sub>2</sub> under 266.104(a), 266.106(c) or (d), or 266.107(b)(2) or (c)	85	270.66(f)(5)					
identification of sources of fugitive emissions and their means of control	85	270.66(f)(6)					
continuous measurement of CO, oxygen, and HC in stack gas	85	270.66(f)(7)					
such other information as Director specifies	85,94	270.66(f)(8)					

dcbif99.rtf - Revised: 9/23/99

#### **DRAFT SPA 20**

# SPECIAL CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1999 (cont'd)

			STATE ANALOG IS:			
CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
85	270.66(g)					
		REFERENCE CITATION	CHECKLIST REFERENCE  FEDERAL RCRA CITATION  CITATION  STATE CITATION	CHECKLIST REFERENCE  FEDERAL RCRA CITATION  CITATION  STATE CITATION  ALENT	CHECKLIST REFERENCE  FEDERAL RCRA CITATION  ANALOGOUS STATE CITATION  ALENT  GENT  LESS STRIN- ALENT  GENT	CHECKLIST FEDERAL RCRA CITATION STATE CITATION ALENT LESS STRIN-GENT GENT

dcbif99.rtf - Revised: 9/23/99

				STATE ANALOG IS:				
FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE	
SUBPART G - INTERIM STATUS								
CHANGES DURING INTERIM STATUS								
add new paragraph regarding the addition of newly regulated units if a revised Part A permit application is submitted on or before the date the unit becomes subject to the new requirements	85	270.72(a)(6)						
add new paragraph regarding the addition of newly regulated units under 270.72(a)(6)	85	270.72(b)(7)						
TERMINATION OF INTERIM STATUS								
insert "which has achieved interim status prior to November 8, 1984, interim status terminates" before "on November 8, 1989"	85,94	270.73(f)						
insert "which has achieved interim status prior to November 8, 1984, interim status terminates" before "on November 8, 1992"	85,94	270.73(g)						

Revision Checklist 85 (February 21, 1991; 56 FR 7134) redesignated the old paragraph (d)(2) as (d)(3) and introduced a new paragraph (d)(2) into the code. Revision Checklist 94 (July 17, 1991; 56 FR 32688) made technical corrections to the February 21, 1991 amendatory language for 261.2 and incorrectly redesignated paragraph (d)(3) as (d)(4) and paragraph (d)(4) as (d)(5). The Federal code, as of February 21, 1991, did not include 261.2(d)(3) or 261.2(d)(4). The technical correction addressed by Revision Checklist 96 (August 27, 1991; 56 FR 42504) fixed this error.

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99

The <u>Federal Register</u> addressed by Revision Checklist 94 designated this paragraph as "261.3(c)(2)(ii)(8)." This is a typographical error; the correct paragraph designation is "261.3(c)(2)(ii)(B)." This error was ultimately corrected by the rule addressed by Revision Checklist 96.

- The internal reference to "\$261.6(a)(3)(iv) through (vi)", as affected by Revision Checklist 135, was incorrect in the July 1, 1997, CFR. The reference should have been "\$261.6(a)(3)(<u>iii</u>) through (<u>v</u>)" to correctly correspond to the deletion of subparagraphs in 40 CFR 261.6(a)(3) by Revision Checklists 112, 135, and 142B. Not all of these checklists made the corresponding changes to the internal references at 40 CFR 261.3(c)(3)(ii)(B) or 266.100(b)(3); therefore, the internal reference has remained incorrect in the CFR since July 1, 1993. Revision Checklist 169 subsequently corrects the internal references at both provisions to also reflect the removal of 40 CFR 261.6(a)(3)(v).
- Note that Revision Checklist 85 made revisions to paragraphs 265.112(d)(2), 265.112(d)(2)(i), 265.112(d)(2)(ii), 265.113(a) and 265.113(b). However, the technical correction addressed by Revision Checklist 96 reversed the revisions made by Revision Checklist 85 and retained the July 1990 <u>CFR</u> language. Thus, States should not make any changes to paragraphs 265.112(d)(2), 265.113(a) or 265.113(b).
- Revision Checklist 112 (57 <u>FR</u> 41566; September 10, 1992) removed and reserved Subpart E of Part 266 and recodified the Subpart E provisions as portions of the new Part 279. States adopting CL112 should disregard these corrections made by Revision Checklists 94 and 96.
- Note that there is a typographical error in the <u>Federal Register</u> addressed by Revision Checklist 94 (56 <u>FR</u> 32692; July 17, 1991). The "§266.4" in the heading should be "§266.40." This error was corrected by Revision Checklist 96 at 56 <u>FR</u> 42512 (August 27, 1991).
- This paragraph was entered into the code by Revision Checklist 85 and was modified by Revision Checklist 96. Subsequently, Revision Checklist 98 issued an administrative stay of the BIF rule as it applies to coke ovens burning certain hazardous wastes from the coke by-products recovery process. This administrative stay was removed by Revision Checklist 105 (57 FR 27880; June 22, 1992). Note also that Revision Checklist 98 incorrectly changed the reference "266.100(b), (c), (d) and (f)" to "266.100(b), (c) and (d)." This error was corrected by Revision Checklist 111 at 57 FR 38564 (August 25, 1992).
- Revision Checklist 112 (57 <u>FR</u> 41566, September 10, 1992) removed and reserved Subpart E of Part 266 and recodified the Subpart E provisions as portions of the new Part 279. To reflect this change, Revision Checklist 112 revised 266.100(b)(1) to refer to Part 279 rather than Subpart E of Part 266.
- This paragraph has also been affected by Revision Checklist 135 (59 <u>FR</u> 38536; July 28, 1994) which corrected an error made by Revision Checklist 112 to the internal references. The reference to 261.6(a)(3)(v)-(viii) should be 261.6(a)(3)(<u>iv</u>)-(<u>vi</u>).
- The revision of the exclusion 40 CFR 261.4(a)(12)(i)&(ii) replaces the provision at 40 CFR 261.6(a)(3)(v) causing it to be removed; therefore, these provisions should be adopted together. States should be aware that adoption of the removal of 40 CFR 261.6(a)(3)(v) without the adoption of the revisions to 40 CFR 261.4(a)(12)(i)&(ii) would make the State potentially broader-in-scope than the Federal requirements. The correction of the internal reference at 40 CFR 261.3(c)(2)(ii)(B) is also optional. Although the revision of the internal reference at 40 CFR 266.100(b)(3) is made pursuant to HSWA authority, it is also optional since the revision should be made only if the revisions to 40 CFR 261.4(a)(12)(i)&(ii) are adopted.

- This paragraph has been affected by the non-BIF Revision Checklist 137 (59 <u>FR</u> 47982, September 19, 1994; 60 <u>FR</u> 242, January 3, 1995). See pre-note 1, •.
- Note that the <u>Federal Register</u> addressed by Revision Checklist 85 designated this paragraph as "266.102(d)(4)(D)." This is a typographical error; the correct designation is "266.102(d)(4)(iv)." See technical correction at 56 <u>FR</u> 32688 (July 17, 1991; Revision Checklist 94).
- There seems to be an error in the <u>Federal Register</u> addressed by Revision Checklist 85. Federal code refers to "particulate matter standard in § 266.111(b)," but 266.111(b) addresses definitions of "direct transfer equipment" and "container," not particulate matter standards. It appears that the Federal code should likely reference 266.105(a) as it does contain a particulate matter standard.
- Note that in the February 21, 1991 rule addressed by Revision Checklist 85, the subparagraph designation was not italicized. This is a typographical error. The August 27, 1991 (56 <u>FR</u> 42504; Revision Checklist 96) technical correction fixes this error.
- Note that the August 27, 1991 <u>Federal Register</u> (Revision Checklist 96), which addressed the technical correction for this citation, has a typographical error; the reference to "266.102(e)(4)(iii)(c)(1) and (2)" in this citation should be "266.102(e)(4)(iii)(C)(1) and (2)."
- Note that in the <u>Federal Register</u> for Revision Checklist 85, the subparagraph designation was <u>not</u> italicized. This is a typographical error. The 56 <u>FR</u> 32688 (July 17, 1991; Revision Checklist 94) technical correction fixes this error.
- Note that the July 1, 1992 CFR inadvertently omitted the text to 266.103(c)(1)(i)-(xiii) and 266.103(c)(3)(ii)-(iii)(C) from the Federal code. States should incorporate these paragraphs, as found in the <u>Federal Register</u> addressed by Revision Checklist 85 (56 <u>FR</u> 7134; February 21, 1991), and amended by Revision Checklist 94 (56 <u>FR</u> 32688; July 17, 1991).
- <sup>18</sup> This paragraph was revised by Revision Checklist 144 (60 <u>FR</u> 33912; June 29, 1995) which is a non-BIF checklist. This checklist removed obsolete rules from the CFR.
- Revision Checklist 144 (60 <u>FR</u> 33912; June 29, 1995), a non-BIF checklist, removed 266.104(f) and (f)(1)-(4) and redesignated the previous 266.104(g)-(i) as 266.104(f)-(h). On February 22, 1994, a Federal court of appeals vacated the standard in 266.104(f); therefore, EPA removed it from the CFR.
- In the <u>Federal Register</u> addressed by Revision Checklist 85, the designation for this subparagraph is 266.104(g)2. This is a typographical error; the correct designation is 266.104(g)(2). See the technical correction at 56 <u>FR</u> 32689 (July 17, 1991; Revision Checklist 94).
- Note that there is an error in the <u>Federal Register</u> for Revision Checklist 111 (57 <u>FR</u> 38558; August 25, 1992) for this rule. The phrase "dispersion modeling to predict the maximum annual average off-site ground level contamination for each" appears twice but should only occur once.

- In the <u>Federal Register</u> addressed by Revision Checklist 85, the designations for these subparagraphs are 266.107(d)(i) and 266.107(d)(ii) (see 56 <u>FR</u> 7225). These are typographical errors. The subparagraphs should be designated 266.107(d)(1) and 266.107(d)(2). See technical corrections at 56 <u>FR</u> 32690 (July 17, 1991; Revision Checklist 94).
- In the <u>Federal Register</u> addressed by Revision Checklist 85, the section designation for regulation of residues is 266.122 (see 56 <u>FR</u> 7227). This is a typographical error and the section should be designated 266.112. Revision Checklist 94 corrects this error at 56 <u>FR</u> 32690 (July 17, 1991).
- Note that Revision Checklist 96 replaced the old paragraph introduced into the code by Revision Checklist 85.
- Note the typographical error in the <u>Federal Register</u> for Revision Checklist 127 [58 <u>FR</u> 59598 (November 9, 1993)]: "FO39" should be "F039" (i.e., should be a zero not an upper case "O").
- Note that Revision Checklist 94 replaced the old Table introduced into the code by Revision Checklist 85.
- Note that Revision Checklist 85 simply makes an announcement concerning the publishing of the Appendix at a future time. The Appendix was actually entered into the code by Revision Checklist 94. Subsequently, sections 7.0 and 9.2 were modified by Revision Checklist 96; section 5.0 was modified by Revision Checklists 111 and 114, and section 6.0 was modified by Revision Checklist 111.
- Note that there are errors in the <u>Federal Register</u> for Revision Checklist 111 (57 <u>FR</u> 38558; August 25, 1992) for this rule. The original titles for these tables in the July 17, 1991 rule (56 <u>FR</u> 32688; Revision Checklist 94) read "µG/M³", not"8G/M³" as indicated in the corrections numbered 11 and 12 on page 38566 of the <u>Federal Register</u> for Revision Checklist 111. The "8G/m³." however, appears in the 1991 <u>CFR</u> and is incorrect. These errors were corrected by Revision Checklist 114 (57 <u>FR</u> 44999, September 30, 1992). The "µG/m³" in the July 16, 1991 <u>Federal Register</u> and the "8G/m³" in the 1991 <u>CFR</u> should read "µg/m³" not "g/m³" as shown at 57 <u>FR</u> 38566 (August 25,1992).
- Note that Revision Checklist 96 replaced the old section 7.0 introduced into the code by Revision Checklist 94.
- Note that Revision Checklist 85 simply makes an announcement concerning the publishing of the Appendix at a future date. The Appendix was actually entered into the code by Revision Checklist 94.
- This appendix was originally introduced by Revision Checklist 94; Revision Checklist 85 merely announced that the appendix would be published at a future date. Revision Checklist 125 removed Part 266 Appendix X and Appendices A, B and C to Appendix X, "Guidelines on Air Quality Models (Revised)" and changed references to the guidelines in Part 266 to refer to 40 CFR Part 51, Appendix W.
- Appendix XIII of part 266 was added by the non-BIF Revision Checklist 137 (59 <u>FR</u> 47982, September 19, 1994; 60 FR 242, January 3, 1995). See pre-note 1, •.

- Note that this is the same section of code which contained the specific Part B information requirements for the Wood Preserving listing (55 <u>FR</u> 50450). Thus, the Part B boilers/industrial furnace requirements were added so that the Part B information requirements for drip pads were inadvertently removed by the rule addressed by Revision Checklist 85 (56 <u>FR</u> 7134; February 21, 1991). On July 1, 1991 (56 <u>FR</u> 30192; Revision Checklist 92) a technical correction was published moving the wood preserving requirements to 270.26.
- States only need to make changes if they have adopted, or plan to adopt, the provisions addressed by Revision Checklist 54 (53 <u>FR</u> 37912), because 270.42 is not required by 271.14 to be part of a State's permitting program.
- The paragraph following 270.42(g)(1)(v) in Federal code, i.e., 270.42(g)(2), is included in the <u>Federal Register</u> for Revision Checklist 85 (56 <u>FR</u> 7237, February 21, 1991). However, no changes were made to the paragraph by the February 21, 1991 rule, so it has not been included in this consolidated checklist.
- Note that Revision Checklist 126 (58 <u>FR</u> 46040; August 31, 1993), amended 270.66(c)(2)(i)&(ii) by replacing the reference to 270.6 with a reference to 260.11 as incorporated by reference at both 260.11 and 270.6.

dcbif99.rtf - Revised: 9/23/99 Printed: 11/19/99